<b>Conforms to Regulation</b>	(EC) No. 1907/2006 (REACH)	, Annex II, as amended by Regulation	(EU) No. 453/2010 -
Estonia			
Date of issue/ Date of revision	: 14-07-2015.	Date of previous issue	: 14-07-2015.

# SAFETY DATA SHEET

VIVA COLOR

### HANSA SILICATE

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### **1.1 Product identifier**

Product name Product description

- : HANSA SILICATE
- : Waterborne silicate paint.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor AS TIKKURILA Liimi 5, 10621, Tallinn, Estonia tel +372 6 501 111 fax +372 6 501 122 email Info.ee@tikkurila.com e-mail address of person : productsafety.ee@tikkurila.com responsible for this SDS

#### 1.4 Emergency telephone number

Telephone number :	: 112 (24h)
National advisory body/Poisor	n Center
Telephone number :	16662 (24h)

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Eye Dam. 1, H318

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification	: Xi; R36
	1 1 1 1

Human health hazards : Irritating to eyes.

1

#### 2.2 Label elements

Hazard pictograms



Signal word
Hazard statements

- : Danger
- : H318 Causes serious eye damage.

Date of issue/Date of revision	14.07.2015 Date of previous issue 14.07.2015. HANSA SILICATE
Precautionary statements	
General	<ul> <li>P102 - Keep out of reach of children.</li> <li>P101 - If medical advice is needed, have product container or label at hand.</li> </ul>
Prevention	<ul> <li>P280 - Wear eye/face protection.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> </ul>
Response	: P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	: Not applicable.
Disposal	: Not applicable.
Hazardous ingredients	: potassium silicate
Supplemental label elements	: Not applicable.

#### 2.3 Other hazards

Other hazards which do : None known. not result in classification

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture				
			Class	sification	
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Notes
potassium silicate	EC: 215-199-1 CAS: 1312-76-1	≥5 - <10	Xi; R41, R38	Skin Irrit. 2, H315 Eye Dam. 1, H318	-
crystalline silica respirable	EC: 238-878-4 CAS: 14808-60-7	≥1 - <3	Xn; R48/20	STOT RE 2, H373 (inhalation)	-
			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

## SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General	: In all cases of doubt, or when symptoms persist, seek medical attention. Show this safety data sheet or label to the doctor if possible.
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 20 minutes. Get medical attention immediately.
Inhalation	: Remove to fresh air.
Skin contact	<ul> <li>Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	: If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious). If significant amounts have been swallowed or if symptoms persist, seek medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Causes serious eye damage.

See Section 11 for more detailed information on health effects and symptoms.

#### 4.3 Indication of any immediate medical attention and special treatment needed

14.07.2015 Date of previous issue

14.07.2015. HANSA SILICATE

None.

## **SECTION 5: Firefighting measures**

			100 A 100
5.1	Extin	guishing	a media

Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, CO <sub>2</sub> , powders or water spray/mist.
Unsuitable extinguishing media	: Do not use a direct water jet that could spread the fire.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	:	This product is not classified as flammable. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous thermal decomposition products	:	When exposed to high temperatures, may produce hazardous decomposition products, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters	r spray to keep fire-exposed containers cool. Do not release runoff from ins or watercourses.
Special protective equipment for fire-fighters	ers should wear appropriate protective equipment and self-contained apparatus (SCBA) with a full face-piece operated in positive pressure

## SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures	:	Avoid direct skin contact with product. Avoid breathing vapor or mist. Provide adequate ventilation. See Section 8 for information on appropriate personal protective equipment.
6.2 Environmental precautions	:	Do not allow to enter drains, water courses or soil.
6.3 Methods and materials for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with water or detergent. Avoid using solvents.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

7.1 Precautions for safe handling	:	Avoid contact with skin and eyes. Avoid breathing vapor. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product.
7.2 Conditions for safe storage, including any incompatibilities	:	Store in original container protected from direct sunlight in a dry, cool and well- ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Recommended storage temperature is +5°C+25°C. Do not allow to freeze. Store in accordance with local regulations.
7.3 Specific end use(s)	:	None.

### SECTION 8: Exposure controls/personal protection

protective equipment.

#### 8.1 Control parameters

**Occupational exposure limits** 

Product/ingredient name	Exposure limit values	
crystalline silica respirable	Töökeskkonna keemiliste ohutegurite piirnormid määrus nr 293 (Estonia, 1/2008). TWA: 0,1 mg/m³ 8 hours. Form: respirable dust	
procedures atmosphere or	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory	

#### **DNELs/DMELs**

No DNELs/DMELs available.

#### **PNECs**

No PNECs available.

#### 8.2 Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn (see Personal protection). Provide a readily-accessible eyewash facility. Comply with the health and safety at work laws.

#### Individual protection measures

indificular protootion mout	
Eye/face protection	: Wear eye/face protection (EN166).
Hand protection	<ul> <li>Wear protective gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.</li> <li>Recommended glove material (EN374):</li> <li>&gt; 8 hours (breakthrough time): nitrile rubber Not recommended: PVA gloves</li> </ul>
Skin protection	: Wear appropriate personal protective clothing to prevent skin contact.
Respiratory protection	: A respirator is not needed under normal and intended conditions of product use. Wear a respirator with type P2 filter during sanding (EN149:2001). Be sure to use an approved/certified respirator or equivalent. Check that mask fits tightly and change filter regularly.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Color	: Various
Odor	: Faint odor.
Odor threshold	: Not relevant for the hazard assessment of the product.
рН	: 11 to 11,4
Melting point/freezing point	: Not available.
Initial boiling point and	: Not available.
boiling range	
Flash point	: Closed cup: Not applicable.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not applicable. Product is a liquid.
Upper/lower flammability or explosive limits	: Not available.

Date of issue/Date of revision	14.07.2015 Date of previous issue	14.07.2015.	HANSA SILICATE	
Vapor pressure	: Not available.			
Vapor density	: Not available.			
Density	: 1,3 to 1,4 g/cm <sup>3</sup>			
Solubility(ies)	: Miscible in water.			
Partition coefficient: n-octano	I/ : Not available.			
Auto-ignition temperature	: Not available.			
Decomposition temperature	: Not relevant for the hazard as	ssessment of the	product.	
Viscosity	: Not relevant for the hazard as	ssessment of the	product.	
Explosive properties	: No explosive ingredients pres	sent.		
Oxidizing properties	: No oxidizing ingredients pres	ent.		

#### 9.2 Other information

No additional information.

SECTION 10: Stability and reactivity		
10.1 Reactivity	:	See Section 10.5.
10.2 Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	Avoid extreme heat and freezing.
10.5 Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents strong acids strong alkalis
10.6 Hazardous decomposition products	:	When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Long term exposure by inhalation may cause respiratory tract irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

#### Acute toxicity

Not classified.

Irritation/Corrosion

Causes serious eye damage.

#### Sensitization

The product is not classified as sensitizing by skin contact, but it contains following preservatives or other biocides which may produce an allergic reaction:

1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazol-3-one

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

**Reproductive toxicity** 

Not classified.

14.07.2015.

Teratogenicity
Not classified.
Specific target organ toxicity (single exposure)
Not classified.
Specific target organ toxicity (repeated exposure)
Not classified.
Aspiration hazard
Not classified.

## **SECTION 12: Ecological information**

Ecological testing has not been conducted on this product. Do not allow to enter drains, water courses or soil.

The product is not classified as environmentally hazardous according to Regulation (EC) 1272/2008.

<b>12.1 Toxicity</b> Not available.	No specific data.		
12.2 Persistence and degradability	: No specific data.		
12.3 Bioaccumulative potential	: No specific data.		
12.4 Mobility in soil			
Soil/water partition coefficient (Koc)	: Not available.		
Mobility	: Not available.		
12.5 Results of PBT and vPvB assessment			
PBT	: Not applicable.		
vPvB	: Not applicable.		

**12.6 Other adverse effects** : Not available.

## **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

#### Product

Methods of disposal

: Remove as much product as possible from the tools before cleaning. Gather residues into waste containers. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

Waste code Waste designation		
Ø8 01 11*waste paint and varnish containing organic solvents or other dangerous substance08 01 12waste paint and varnish other than those mentioned in 08 01 11		
If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.		
Packaging		
Methods of disposal	: Empty packaging should be recycled or disposed of in accordance with national	

Methods of disposal	: Empty packaging should be recycled or disposed of in accordance with national regulations.

Special precautions : No additional information.

14.07.2015.

## **SECTION 14: Transport information**

This product is not regulated for carriage according to ADR/RID, IMDG.

	ADR/RID	IMDG
14.1 UN number	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-
14.3 Transport hazard class(es)	-	-
14.4 Packing group	-	-
14.5 Environmental hazards	No.	No.
Additional information	-	-

**14.6 Special precautions for user**: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Other EU	regulations
Europe	inventory

- : Not determined.
- **VOC Directive** : This product is in scope of Directive 2004/42/CE.

: Not available.

15.2 Chemical Safety<br/>Assessment: This product contains substances for which Chemical Safety Assessments are still<br/>required.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.
 Abbreviations and

 ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 vPvB = Very Persistent and Very Bioaccumulative

 Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

#### Classification

Eye Dam. 1, H318

Justification

Calculation method

Date of issue/Date of revision	14.07.2015 Date of previous issue 14.07.2015. HANSA SILICATE
Full text of abbreviated H statements	<ul> <li>H315 Causes skin irritation.</li> <li>H318 Causes serious eye damage.</li> <li>H373 May cause damage to organs through prolonged or repeated exposure if (inhalation) inhaled.</li> </ul>
Full text of classifications [CLP/GHS]	: Eye Dam. 1, H318 Skin Irrit. 2, H315 STOT RE 2, H373 (inhalation) SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (inhalation) - Category 2
Full text of abbreviated R phrases	<ul> <li>R48/20- Harmful: danger of serious damage to health by prolonged exposure through inhalation.</li> <li>R41- Risk of serious damage to eyes.</li> <li>R36- Irritating to eyes.</li> <li>R38- Irritating to skin.</li> </ul>
Full text of classifications [DSD/DPD]	: Xn - Harmful Xi - Irritant
Date of issue/ Date of revision	: 14-07-2015.
Date of previous issue	: 14-07-2015.
Version	: 1.01
Notico to reador	

#### Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 453/2010 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.