# Special Solvent Spray

**Paint Thinner** 

- Fast evaporation during drying
- Low odor



TECHNICAL DATA		
Fields of application	Solvent for thinning alcyd paint and lacquers before high-pressure sprayer. Suitable also for cleaning tools, details, parts, cleaning of items made from natural material and cleaning of small surfaces	
Storage	Unaffected by cold storage or transport.	
Storage time	In tightly closed original container until best before date (stated on can).	
Density	0,7 kg/l, (ISO 12185).	
Packaging	0,5L; 1,0L	



# **INSTRUCTIONS FOR USE**

### THINNING

Use Special Solvent Spray according to the instructions stated on paint product label.

## **CLEANING OF PAINTING TOOLS**

Clean painting tools immediately after finishing work from liquid paint or lacquer residues, wash with *Special Solvent Spray*.

### **CLEANING OF SURFACE**

Suitable for cleaning painted, wooden and metal surfaces from residues of oil, grease or resin. When cleaning painted surface, test suitability of Special Solvent Spray on small surface area.

Cleansing solution preparation: ad 0,1litres of Special Solvent Spray into 10 litres soap or other detergent solution.

### **ENVIRONMENTAL, SAFETY AND WASTE REGULATORY**



#### Danger

UN 1268

Contains: Hydrocarbons, C7, n-alkanes, isoalcanes, cyclics. EU number 927-510-4. Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Keep away from heat/ sparks/open flames/hot surfaces. — No smoking. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/ face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Store in a well-ventilated place. Keep container tightly closed. Keep out of reach of children.

Do not discharge the product into sewerage systems, watercourse, nor pour it onto the ground. Dry and empty containers should be recycled or discarded in compliance with the local regulations. Liquid waste should be discarded according to the local regulations

#### TRANSPORTATION

Unaffected by cold storage or transport.

ADDITIONAL PRODUCT INFORMATION www.vivacolor.ee

The data above is verified, it is correct and based on the laboratory tests as well as on practical experience. Our management system is certified according to international standards ISO 9001 and ISO 14001. As a producer, we cannot be held responsible for any losses incurred upon incompliance with the technical data sheets or application terms for a particular product. AS TIKKURILA Liimi 5, 10621 Tallinn, Estonia, tel +372 650 11 11, fax +372 650 11 22, e-mail: info.ee@tikkurila.com

