



TIKKURILA

VALTTI PRIMER

PRIMING COMPOSITION.

**DESCRIPTION**

Colorless priming composition containing oil for outdoor wood treatment.

RECOMMENDED USES

For treatment of all wooden structures which should be further painted with finish coat (except oils for wood and paints based on red ochre).

PRODUCT FEATURES

For outdoor protection and wooden structures priming before finishing painting. For sawn, planed wood and log, including heat-treated and impregnated under pressure. Has a high penetrating ability, protects the wood from bio-damage (blue and mold). Colorless primer does not protect the wooden surface from sunlight, so it is recommended to apply the finishing coat as soon as possible.



TIKKURILA

VALTTI PRIMER

TECHNICAL DATA

Colour Shades	Colorless.
Gloss	NA
Coverage	Planed surfaces: 8-10 m ² /l; Sawn wood surfaces: 4-5 m ² /l.
Can sizes	0.9 l, 2.7 l, 9 l
Application method	Brush, spray or dip.
Drying time (23°C and 50% relative air humidity)	Touch-dry after approx. 30 min. Recoatable after 24 hours. Attention! In case of low temperatures and high air relative humidity, the drying time may be increased.
Density (kg/l)	about 0,8 kg/l.
Volume solids (%)	15%.
Storage	In tightly closed package, protecting from moisture, heat and direct sunlight. Can withstand storage at low temperatures. In case of storage at subzero temperatures before use the paint should be hold at (+20±2)°C for 24 hours and carefully stirred. Shelf life - 60 months from the production date in unopened original packaging.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

VALTTI PRIMER

APPLICATION INSTRUCTIONS

Application conditions

The treated surface should be dry and clean. During application and drying of the product, the temperature must be above +5°C and relative air humidity should be lower than 80%.

Attention! In case of low temperatures and high air relative humidity, the drying time may be increased.

Surface preparation

Clean the surface from dirt, dust and other impurities. Wash contaminated and moldy areas with Tikkurila «Homeenpoisto», observing the instructions for use. Protect unpainted surfaces and plants from splashes of primer Tikkurila «Valtti Primer».

Priming

To treat the surface with primer Tikkurila «Valtti Primer» in the early stage of construction. Stir primer before and during use. Apply liberally with a brush, spray or dip. The end ends of the wood are treated with special care.

Finish coating to make as soon as possible, but not earlier, than in 24 hours after priming. If the painting is delayed, it is recommended to repeat priming with Tikkurila Tikkurila «Valtti Primer». Protect unpainted surfaces and plants from splashes.

Cleaning of tools

Clean tools with Tikkurila «White Spirit 1050».

Environmental protection and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations. Note! Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials can create fire some hours later and should be soaked in water and placed in a closed metal container before disposal.

Health and Safety

Contains: hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, 2-octyl-2H-isothiazol-3-one (OIT). **DANGER.** Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from sparks and open flames. - No smoking. Do not breathe vapor. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves. **IF SWALLOWED:** Immediately call a POISON CENTER or physician. Do NOT induce vomiting. **IF ON SKIN:** Wash with plenty of soap and water. This primer contains a biocidal product for the preservation of the surface treatment. Contains: 2-octyl-2H-isothiazol-3-one (OIT) and 3-iodo-2-propynyl butylcarbamate (IPBC).



GHS02

GHS07

GHS08

GHS09

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.