

Ceiling 2

Ceiling paint

- ✓ Easy to paint
- ✓ Non-reflecting
- ✓ Non-dripping
- ✓ Even result
- ✓ Excellent coverage
- ✓ Prolonged drying time - low roller pattern

Certified
by the Nordic Swan Ecolabel



Approved by
Estonian Allergy Federation; Lithuanian society
of pulmonology and allergy;
Latvian Asthma and Allergy Association



TECHNICAL DATA	
Product information	Deep matt (2) waterborne white paint for ceilings. It helps you to paint easily a smooth ceiling surface with no reflections.
Fields of application	Ceilings in dry premises (bedrooms, children's rooms, living rooms, halls, offices, schools, kindergartens and other public premises). Suitable for painting new and previously painted concrete, plaster-treated, filler-treated or wallpapered surfaces, plaster blocks, gypsum boards, primed fiberboard and cardboard surfaces.
Gloss	Deep matt (2).
Coverage per coat	8-10 m ² /l smooth surfaces, 4-6 m ² /l gypsum boards and filler-treated rough surfaces.
Tinting	Paint can be used white or tinted in light shades (base A) according to <i>Tikkurila</i> interior color cards. Shade accuracy is not complete. Tinted products cannot be returned or exchanged.
Application method	To be applied with roller, painting brush or high-pressure airbrush. The high-pressure airbrush nozzle shall be 0,017" - 0,021" or 0,460 - 0,530 mm.
Suggested working tools	<i>Anza rollers Basic Rilon.</i>
Drying time at +23 °C, RH 50%	Touch dry - 0,5 hours, recoatable - 1-2 hours.
Thinner	Water. The amount of thinner may be up to 10% of the paint volume.
Cleaning of painting tools	Clean painting tools from liquid paint residues, wash with soap and water.
Storage	Protect the product from frost!
Storage time	In tightly closed original container until best before date. Production/ best before dates are stated on a can. Reseal once opened cans well for next use.
Solid content	About. 35% v/v.
Density	1,3 kg/l.
Wet scrub resistance	Class 2, ISO 11998, 200 cycles 5-20 microns.
Resistance to chemicals	Resistant to short-term exposure to household cleansers and weak solvents (white spirit).
Packaging	0,9 L; 2,7 L; 7,2 L; 11,7L, 18L.



INSTRUCTIONS FOR USE

PREPARATION

Unpainted surfaces:

Clean the surface from dust and dirt. Use suitable filler from *Vivacolor* series to treat uneven surface, sand the surface and remove the dust formed. Filler-treated, porous or non-uniformly absorbing surfaces, as well as fibreboard- or cardboard surfaces shall be primed with waterborne priming paint *Vivacolor 1*. Prime metal surface (e.g. nail heads) with priming paint for metals *Universal Korrostop* or *Universal Korrostop+*. Use alkyd priming paint *Special Primer* to prime surfaces treated with chalk-based whiting putty. When using any priming paint, follow relevant guidance for the product's use. Using priming paint will reduce consumption of topcoat paint and improve adhesion between surface and topcoat.

Previously painted surfaces:

Remove residues of old loose paint. Clean the surface with cleansing agent *Special Clean*, rinse it with water and allow to dry. Sand glossy and hard surface until matt, remove dust. Weak and dusty surfaces should be treated with alkyd priming paint *Special Primer*. Use suitable filler from *Vivacolor* series to treat chinks and cracks, sand the surface and remove the dust formed. Use 10% diluted paint to prime the filler-treated surface.

PAINTING CONDITIONS

Surface should be clean and dry, temperature of ambient air should be above +5°C and relative air humidity lower than 80%. Avoid draught and high temperatures during painting.

PAINTING

Thoroughly mix paint before painting, thin with water if required up to 10% of volume. Apply 1 or 2 layers with roller, brush or airbrush.

CARE AND HANDLING OF SURFACE

The surfaces can be cleaned in 1 month after painting. To clean the surface, use a sponge or a cloth, moistened with water or a solution of a neutral cleansing agent (pH 6-8). To clean heavily soiled surfaces, use a sponge or a cloth, moistened with the solution of a low-alkali cleansing agent (pH 8-10). After cleaning, rinse the surface with clean water. On preparing the solution, follow the manufacturer's instruction. After painting, the surfaces should not be heavily loaded, for under normal conditions the painted surface will gain its ultimate endurance and resistance to wear in approximately 1 month after painting. If the surface still needs cleaning prior to this time, it can be delicately cleaned with a sponge or cloth, moistened with water.

ENVIRONMENTAL, SAFETY AND WASTE REGULATORY

Do not discharge the product into sewerage systems, watercourse, nor pour it onto the ground. Liquid waste should be discarded according to the local regulations. Dry and empty containers should be recycled or discarded in compliance with the local regulations.

Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of: 5-chloro- 2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. Wear protective gloves. This product contains a biocidal product for the preservation of the product during storage. Contains C(M)IT/MIT (3:1).

EU VOC limit value (subgroup A/a): 30 g/l. Maximum content of VOC in product 10g/l.

TRANSPORTATION

Protect from frost!

ADDITIONAL PRODUCT INFORMATION

www.vivacolor.ee/lv/lt

PAINT LINE INFO

Locally optional

The data above is verified and correct, based on the laboratory tests as well as on practical experience. Our management system is certified according to the international standards ISO 9001 and ISO 14001. As a producer, we cannot be held responsible for any losses incurred upon incompliance with the technical data sheets or application terms for a particular product.

AS TIKKURILA Liimi 5, 10621 Tallinn, Estonia, tel +372 650 11 11, fax +372 650 11 22, e-mail: info.ee@tikkurila.com

