



Orient Chinese Wood Oil

Orient Chinese wood oil is a first-class oil with extremely good qualities regarding penetration deeply into the wood.

Chinese wood oil has since ancient times been used to protect wood from moisture penetration. The oil's fine quality is – due to the size of the molecules – more penetrating.

Intended for weather protection of all wood, even exotic woods. The product is suitable for prime treatment as well as maintenance of garden furniture, decks, windows, façades and joinery.

It is also intended to bind dust and to emphasize the lustre on floor tiles and bricks.

Furthermore it is intended as treatment upon deck and inside boats. When applying several coats, the oil needs to be thoroughly dry between the layers.

Orient Chinese wood oil is produced in Sweden.

Pre-painting

- Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint.
- The air and surface temperature is also important for the end result. Do not paint if it is below +5°C.
- The surface must be clean, dry and firm. Brush or scrape off loose old paint and/or porous and degraded wood.

Painting

- The oil is to be thoroughly penetrating the material until the surface stops to absorb the oil. Wait a few minutes and then wipe off excess oil with a cloth or a sponge, since the oil is supposed to penetrate into the surface, not form a film on top.
- Due to the high dry content, the oil is not suitable as prime oil for later recoating with paint.
- Apply with brush, sponge or cloth.

Post-painting

- Wipe off the tools thoroughly before cleaning with white spirit. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point.
- **N.B.!** Cloths soaked in oil may spontaneously combust and must therefore be neutralised.

Maintenance

- Repeat the treatment when the surface appears to be dry. Sunlit and not fully absorbed wood may need treatment a couple of times pro year.

Technical data			
Use	Outdoors	Class of flammability	3
Binder	Tung tree oil/alkyd/linseed oil	Storage time	2 years if unopened, frost free storage
Gloss	Dependent on surface	Air/surface temperature by painting	Minimum +5°C
VOC-Category	(Cat. A/f): 700 g/l (2010)	Consumption	4–10 m ² /L.
Cleaning of tools	White spirit/Naphtha	Application	Brush, sponge or cloth
Dilution	White spirit/ Naphtha		1, 3, and 10 Litres.
Drying time	24–48 hours dust dry	Package	Also available in barrels of 200L.
(depending on air/surface temp.)	48 hours re-paintable	In stock	1 and 3 L. = Yes



The information in this data sheet is based on laboratory tests and practical experience. Since the conditions, under which the product is used, are beyond our control, we can only guarantee the quality of the product itself. The end-result depends on the surface, preparation, temperature, humidity and execution etc.

Please check our web site to make sure that this Product data sheet is valid.