

Light Pine Tar Oil

Thin-bodied wood oil

General

Light Pine Tar oil is thin-bodied tar oil which is based on Genuine Pine Tar and the finest Gum Turpentine.

Light Pine Tar oil penetrates deep into the wood, preventing it from drying out and splitting. The tar protects effectively against water penetration and delays the degradation of the timber. Light Pine Tar oil is dark brown when painting but the colour will eventually fade away as the UV rays break down the tar on the surface. This whole process can take up to a few months before the entire surface has returned to the colour that was before painting.

The marked smell of tar subsides after a few days and after a month the scent is barely noticeable. You may walk on the surface as soon as all **Light Pine Tar oil** has penetrated into the wood.

Pine Tar is nature's own wood protection and consists among others various kinds of resins and terpenes. Resins are the tree's natural way of protecting themselves against micro-organisms and heal injuries. Terpenes are a solvent and it accelerates the drying process. Pine Tar is produced of resin-rich pine trees in furnace.

Range of application

Light Pine Tar oil is mainly used for pressure-treated wood on terraces, garden furniture, bridges and otherwise untreated wood outdoors where the surface requires a low viscosity tar product.

Instructions for use

For best result use **Light pine Tar oil** during warm weather, at least 10 degrees Celsius. The product becomes then more convenient and penetrates into the surface. Stir in the jar before painting.

You can paint on pressure-treated wood that has been out for 1-2 years. Light Pine Tar Oil will then be better able to penetrate into the wood. Treatment of terraces should preferably take place at least every two years.

Light Pine Tar oil shall not be painted on wood previously treated with other solid colors types.

Painting:

Brush off dust and dirt. Wash off algae and mold growth. Previously, surfaces that have been treated with ordinary wood oil must first be washed away. The surface must be dry before painting. Use a brush or roller. Can also be syringed. Wipe off any excess with a rag soaked in turpentine or alcohol.

Ensure good ventilation. Painting outdoors. Material Safety Data Sheet will be found at www.auson.se and painting instructions at www.tjarlek.se

Package

60700401 / 1-lit can
60700472 / 3 lit can

Technical data

Color:	Light brown
Density:	0,91 + 0,03 kg/lit
Dry content:	50%
Coverage:	6 -10 m ² / lit depending on the kind of base.
Drying Time:	From several days to several weeks depending on the weather, planed or unplanned lumber, wood, thickness and how well the tar seeped into the surface.
Thinning:	Gum turpentine NB! Do not use White Spirit
Cleaning:	Gum Turpentine, Alcohol or soap and water
Storage:	24 Months (Unopened jar)

For further information we recommend the safety data sheet or instruction on package.

Issue: 2016-11-10 / AA



Auson AB, Kungsbacka, Sweden
T: +46 (0)300-56 20 00
www.auson.se

Dessa anvisningar och information är avsedda att vägleda förbrukaren vid användning av produkten och lämnas utan förbindelse. Vid oklarhet tillråds egna prov eller skriftliga råd från oss.