

## SAFETY DATA

SHEET Edition: 7 November 2017  
Trade name: SketchPaint Can A  
Page: 1/17  
Version: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking.

#### 1.1. Product identifier

Trade name: **SketchPaint Can A**  
Synonym: Whiteboard paint – Dry-erase paint

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

A smooth surface treated with SketchPaint is writable and erasable with most whiteboard markers.  
Component of a two-component product.  
Product category: PROC19 (Hand-mixing),  
PROC10 (Roller application or brushing).

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer/supplier: MagPaint Europe B.V.  
Riezenweg 2  
7071 PR Ulft  
THE NETHERLANDS  
Tel.: +31 (0) 315 38 64 73  
Email: info@magpaint.com  
Website: www.magpaint.com

#### Further information obtainable from:

Contact person: Mike Poorthuis  
Tel.: +31 (0) 315 38 64 73  
Email: info@magpaint.com  
Working hours (business days): 09h00-17h00

#### 1.4. Emergency telephone number

The Netherlands: Nationaal Vergifingen Informatie  
Centrum (NVIC): +31 (0) 30 247 88 88  
Belgium: Belgian Poison Centre: +32 (0) 70 245 245  
United Kingdom: UWIC: +44 (0) 29 204 16388

### SECTION 2: Hazards identification.

#### 2.1. Classification of the substance or mixture

Classification in accordance with Regulation (EC) no 1272/2008  
Acute Tox. 4; H332 - STOT SE3; H335 - Skin Sens. 1; H317 - Eye Dam. 1; H318 - H412.

#### 2.2. Label elements



Hazard pictograms:

Signal word:

Danger.

Hazard statements:

H317

May cause an allergic skin reaction.

H318

Causes serious eye damage.

H332

Harmful if inhaled.



## SAFETY DATA

SHEET Edition: 7 November 2017  
Trade name: SketchPaint Can A  
Page: 2/17  
Version: 1.2

H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
(EUH204)	Contains isocyanates. May produce an allergic reaction.)
Precautions:	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container to hazardous or special waste collection point.
Hazard-determining components for labelling:	Hexane, 1,6-diisocyanato-, homopolymer and polyoxyethylene tridecyl ether phosphate.
2.3. Other hazards	Contains isocyanates. Wear eye / face protection. Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.
Results of PBT and vPvB assessment	
PBT:	No.
vPvB:	No.

## SECTION 3: Composition/information on ingredients.

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

Chemical description: Preparation comprising the following component(s) and (other) unclassified components.

Hexane, 1,6-diisocyanato-, homopolymer

CAS#: 28182-81-2

EC#: 931-274-8

Index#: -

REACH reg.#: 01-2119485796-17

Content (W/W): 50 - 70 %

Danger, 1272/2008/EC: Acute Tox. 4; H332 - STOT SE3; H335 - Skin Sens. 1; H317



## SAFETY DATA

SHEET Edition: 7 November 2017  
Trade name: SketchPaint Can A  
Page: 3/17  
Version: 1.2

Polyoxyethylene tridecyl ether phosphate	
CAS#:	9046-01-9
EC#:	polymer
Index#:	-
REACH reg.#:	-
Content (W/W):	1 - < 10 %
Danger, 1272/2008/EC:	Skin Irrit. 2; H315 - Eye Dam. 1; H318 - Aquatic Chronic 2; H411
Ethyl-diisopropylamine	
CAS#:	7087-68-5
EC#:	230-392-0
Index#:	-
REACH reg.#:	-
Content (W/W):	0.1 - 2 %
Danger, 1272/2008/EC:	Skin Corr. 1 B; H314 - Acute Tox. 4; H302 - Flam. Liq. 2; H225 - Aquatic Chronic 3; H412
Phosphoric acid, butyl ester	
CAS#:	12788-93-1
EC#:	235-826-2
Index#:	-
REACH reg.#:	-
Content (W/W):	0.1 - 2 %
Danger, 1272/2008/EC:	Skin Corr. 1 B; H314
Hexamethylene-1,6-diisocyanate	
CAS#:	822-06-0
EC#:	212-485-8
Index#:	615-011-00-1
REACH reg.#:	01-21194457571-37
Content (W/W):	0.1 - 0.4 %
Danger, 1272/2008/EC:	Acute Tox. 1; H330 - Resp. Sens. 1; H334 - Acute Tox. 4; H302 - Skin Irrit. 2; H315 - Eye Irrit. 2; H319 - Skin Sens. 1; H317 - STOT SE3; H335
Note:	Specific concentration limits, Resp. Sens. 1; H334, Skin Sens. 1; H317 ≥ 0,5.
Full text of H- and EUH-phrase(s):	See section 16.

## SECTION 4: First aid measures.

### 4.1. Description of first aid measures

General information:	If in doubt or if symptoms persist, seek medical attention. Use suitable protective equipment to treat a contaminated person.
Eye contact:	Place contaminated clothing in a sealed bag for disposal. Reacts with aqueous humour. Immediately flush eyes thoroughly with water (for at least 15 minutes) while holding eyelids open. Then immediately consult a physician/ophthalmologist.
Skin contact:	Remove contaminated clothing immediately. Immediately wash



## SAFETY DATA

SHEET Edition: 7 November 2017  
Trade name: SketchPaint Can A  
Page: 4/17  
Version: 1.2

Ingestion:	exposed skin with polyethylene glycol or, if not available, with plenty of water and soap. Do not use solvents or thinners. If persistent irritation or sensitization occurs, consult a physician/skin specialist. If swallowed, get medical attention immediately. Keep at rest. Have person rinse mouth thoroughly with water, spit out rinse water. Do NOT induce vomiting.
If aerosol or vapour is inhaled in high concentrations:	Take the person into the fresh air and keep him warm. Avoid physical exertion. Seek medical advice immediately. Show this safety data sheet to the doctor. NEVER attempt to induce vomiting. Have person rinse mouth thoroughly with water, spit out rinse water. Do not give anything to drink. Administer artificial respiration if breathing is irregular or has stopped. Do not give anything to eat or drink. Loosen tight clothing such as a shirt collar, tie, belt or waistband. If unconscious, place in recovery position and seek medical advice.
4.2. Most important symptoms and effects, both acute and delayed	
Inhalation:	Dry/sore throat. Coughing. Irritation of the respiratory tract. Nasal irritation. Runny nose. Risk of asphyxiation in confined spaces. The product contains isocyanates. Given the properties of this component, and considering the toxicological data available on similar preparations, the product may cause acute irritation and / or sensitization of the respiratory tract. Asthma symptoms, breathing difficulties or chest tightness may occur. Exposure to vapour concentrations above the occupational exposure limit may result in adverse effects such as irritation of the mucous membranes and the respiratory tract, kidney and liver disorders and disorders of the central nervous system. Signs and symptoms of exposure include coughing, headaches, shortness of breath, tightness in the chest, transient flu-like symptoms. The effects may be delayed for hours (Risk of inflammation of the respiratory tract. Risk of pulmonary oedema. Breathing difficulties).
Skin contact:	Tingling / irritation of the skin.
Eye contact:	Reacts with aqueous humour. Irritating. Lacrimation.
Ingestion:	Primary irritation of mucous membranes: Irritating.
4.3. Indication of any immediate medical attention and special treatment needed	
Further medical treatment:	Symptomatic treatment and supportive therapy as prescribed. Symptomatic treatment (decontamination, control of vital functions). No specific antidote known. To prevent pulmonary oedema: corticosteroid-containing dosing aerosol.

## SECTION 5: Firefighting measures.

### 5.1. Extinguishing media

Suitable extinguishing media: Use CO<sub>2</sub>, ABC powder, alcohol-resistant foam or water spray.  
Unsuitable extinguishing media for safety reasons: The material reacts with water, do not use direct water stream.



## SAFETY DATA

SHEET Edition: 7 November 2017  
Trade name: SketchPaint Can A  
Page: 5/17  
Version: 1.2

### 5.2. Special hazards arising from the substance or mixture

#### Special hazards:

Fire will produce dense black smoke. Wear respiratory protection. Exposure to decomposition products may be a hazard to health. In case of fire, hazardous and toxic vapours may be released, such as carbon dioxide, carbon monoxide, hydrogen cyanide, nitrogen oxides, isocyanate.

### 5.3. Advice for firefighters

#### Protection of fire-fighters:

For fire-fighters, mouth and nose protection with independent air supply (breathing apparatus) and full (chemical) protective clothing are mandatory. Use qualified personnel who are well aware of the dangers of this product. After use, clean the equipment thoroughly (shower, clean clothing thoroughly and check suitability).

#### Additional information:

If closed containers are exposed to fire, keep cool with water. Avoid direct contact of liquid with water. Prevent fire-fighting water from entering the sewage system. Stay upwind.

## SECTION 6: Accidental release measures.

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear appropriate personal protective equipment, including safety glasses, personal protective clothing and chemical resistant gloves when cleaning up major spillages. Ventilate the area. Avoid inhalation of vapours. Avoid skin and eye contact. Keep people at a distance and stay upwind.

### 6.2. Environmental precautions

Prevent product from entering sewers or surface water. If this should occur, inform the local authorities. Do not allow to enter the soil or subsoil.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The area should be immediately cleaned with a suitable detergent. Such a detergent or neutralising agent can be made by mixing: water (95%)/8% ammonia solution and liquid soap (2%). Alternatively, half of the water may be replaced by ethanol or isopropyl alcohol. Also add the above mixture to the spill and leave it in an unsealed container for several days.

### 6.4. Reference to other sections

Information regarding safe handling – see section 7.  
Information regarding personal protective equipment – see section 8.  
Information regarding disposal – see section 13.

## SECTION 7: Handling and storage.

### 7.1. Precautions for safe handling



**SAFETY DATA**

**SHEET Edition:** 7 November 2017  
**Trade name:** SketchPaint Can A  
**Page:** 6/17  
**Version:** 1.2

<p><b>Handling:</b></p>	<p>When handling observe the usual precautionary measures for chemicals. Strict hygiene is required. See section 8 for personal protection. Persons suffering from asthma, allergies or chronic or acute disorders of the respiratory tract, should not handle this product. Skin and eye contact, as well as inhalation of vapour, should be avoided. Do not smoke, eat or drink in the working area. Provide ventilation/exhaust ventilation in closed workspaces. When spraying, use respiratory protection. Protect from moisture. Fresh products made from isocyanates may contain unreacted isocyanates and other dangerous substances. Keep container tightly closed. Contact with water and moist air generates CO<sub>2</sub>, which generates pressure in sealed containers. Danger of bursting when container is sealed gas-tight. Re-open used containers with caution.</p>
<p><b>7.2. Conditions for safe storage, including any incompatibilities</b></p>	
<p><b>Storage:</b></p>	<p>Keep container tightly closed in a cool, dry, well-ventilated place. Protect from moisture. In combination with moisture, CO<sub>2</sub> overpressure may develop. Keep away from heat and direct sunlight. Keep away from water, oxidants, amines, polyols and strong bases and acids. Keep away from food, stimulants and animal feeding stuffs. Do not smoke. Make sure that the product is not accessible to unauthorized persons. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Fill space above liquid level preferably under dry nitrogen.</p>
<p><b>Requirements to be met by storerooms and receptacles:</b></p>	<p>Preferably keep in the original packaging.</p>
<p><b>Packaging material, suitable:</b></p>	<p>Original container, coated can, stainless steel, polyethylene.</p>
<p><b>Packaging material, unsuitable:</b></p>	<p>Paper, cardboard, copper, copper alloys, brass, tin.</p>
<p><b>Information about storage in one common storage facility:</b></p>	<p>Keep away from oxidants, strong bases and acids, protic solvents, amines and alcohols.</p>
<p><b>Further information about storage conditions:</b></p>	<p>Recommended storage temperature 1 - 49 °C.</p>
<p><b>7.3. Specific end use(s)</b></p>	<p>No further relevant information available.</p>

**SECTION 8: Exposure controls/personal protection.**

**8.1. Control parameters**

Ingredients with limit values that require monitoring at the workplace:		
Product information: CAS#: 822-06-0	Hexamethylene diisocyanate/hexamethylene-1,6-diisocyanate	
TWA 8 h	mg/m <sup>3</sup> (ppm)	0.04 (-) formerly Dutch value 0.034 (0.005) Belgium 0.035 (0.005) Germany, Denmark, Norway, Austria, Spain 0.02 (0.002) Sweden 0.02 (-) Switzerland 0.075 (0.01) France
TWA 15 minutes		0.14 (-) formerly Dutch value 0.15 (0.02) France 0.035 (0.005) Austria 0.03 (0.005) Sweden 0.02 (-) Switzerland



**SAFETY DATA**

SHEET Edition: 7 November 2017  
 Trade name: SketchPaint Can A  
 Page: 7/17  
 Version: 1.2

Dangerous ingredients with DN(M)EL:				
Product information:	Exposure	Value	Unit	Population / Effects
Hexane, 1,6-diisocyanato-, homopolymer CAS#: 28182-81-2				
DN(M)EL	Short-term dermal	-	mg/kg bw/day	Workers Local
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	Workers Local
DN(M)EL	Short-term dermal	-	mg/kg bw/day	Workers Systemic
DN(M)EL	Short-term inhalation	1	mg/m <sup>3</sup>	Workers Systemic
DN(M)EL	Long-term dermal	-	mg/kg bw/day	Workers Local
DN(M)EL	Long-term inhalation	0.5	mg/m <sup>3</sup>	Workers Local
DN(M)EL	Long-term dermal	-	mg/kg bw/day	Workers Systemic
DN(M)EL	Long-term inhalation	-	mg/m <sup>3</sup>	Workers Systemic
DN(M)EL	Short-term dermal	-	mg/kg bw/day	General population Local
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	General population Local
DN(M)EL	Short-term dermal	-	mg/kg bw/day	General population Systemic
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	General population Systemic
DN(M)EL	Short-term Oral	-	mg/kg bw/day	General population Systemic
DN(M)EL	Long-term dermal	-	mg/kg bw/day	General population Systemic
DN(M)EL	Long-term inhalation	-	mg/m <sup>3</sup>	General population Systemic
DN(M)EL	Long-term oral	-	mg/kg bw/day	General population Systemic
DN(M)EL	Long-term dermal	-	mg/kg bw/day	General population Local
DN(M)EL	Long-term inhalation	-	mg/m <sup>3</sup>	General population Local
Dangerous ingredients with DN(M)EL:				
Product information:	Exposure	Value	Unit	Population / Effects
Hexamethylene diisocyanate/ hexamethylene-1,6-diisocyanate				



**SAFETY DATA**

SHEET Edition:

7 November 2017

Trade name:

SketchPaint Can A

Page:

8/17

Version:

1.2

CAS#: 822-06-0				
DN(M)EL	Short-term dermal	sensitizing	mg/kg bw/day	Workers Local
DN(M)EL	Short-term inhalation	0.07	mg/m <sup>3</sup>	Workers Local
DN(M)EL	Short-term dermal	sensitizing	mg/kg bw/day	Workers Systemic
DN(M)EL	Short-term inhalation	0.07	mg/m <sup>3</sup>	Workers Systemic
DN(M)EL	Long-term dermal	sensitizing	mg/kg bw/day	Workers Local
DN(M)EL	Long-term inhalation	0.035	mg/m <sup>3</sup>	Workers Local
DN(M)EL	Long-term dermal	sensitizing	mg/kg bw/day	Workers Systemic
DN(M)EL	Long-term inhalation	0.035	mg/m <sup>3</sup>	Workers Systemic
DN(M)EL	Short-term dermal	-	mg/kg bw/day	General population Local
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	General population Local
DN(M)EL	Short-term dermal	-	mg/kg bw/day	General population Systemic
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	General population Systemic
DN(M)EL	Short-term Oral	-	mg/kg bw/day	General population Systemic
DN(M)EL	Long-term dermal	-	mg/kg bw/day	General population Systemic
DN(M)EL	Long-term inhalation	-	mg/m <sup>3</sup>	General population Systemic
DN(M)EL	Long-term oral	-	mg/kg bw/day	General population Systemic
DN(M)EL	Long-term dermal	-	mg/kg bw/day	General population Local
DN(M)EL	Long-term inhalation	-	mg/m <sup>3</sup>	General population Local

**Dangerous ingredients with PNEC:**

Product information:	Value	Unit	Compartment
Hexane, 1,6-diisocyanato-, homopolymer CAS#: 28182-81-2			
PNEC	0.127	mg/l	Fresh water
PNEC	0.0127	mg/l	Marine water
PNEC	1.27	mg/l	Intermittent releases
PNEC	38.28	mg/l	STP (sewage treatment plant)
PNEC	266.7	g/kg dwt	Sediment fresh water





**SAFETY DATA**

SHEET Edition: 7 November 2017  
 Trade name: SketchPaint Can A  
 Page: 9/17  
 Version: 1.2

PNEC	-	mg/kg dwt	Sediment marine water
PNEC	53.2	g/kg wwt	Soil
PNEC	-	mg/l	Oral

Dangerous ingredients with PNEC:			
Product information:	Value	Unit	Compartment
Hexamethylene diisocyanate/ hexamethylene-1,6-diisocyanate CAS#: 822-06-0			
PNEC	0.0774	mg/l	Fresh water
PNEC	0.00774	mg/l	Marine water
PNEC	0.774	mg/l	Intermittent releases
PNEC	8.42	mg/l	STP (sewage treatment plant)
PNEC	0.01334	mg/kg dwt	Sediment fresh water
PNEC	0.001334	mg/kg dwt	Sediment marine water
PNEC	0.0026	mg/kg wwt	Soil
PNEC	-	mg/l	Oral

**8.2. Exposure controls**

Note:

Material is part of a two-component system. For exposure controls, see also section 8 of the safety data sheet of SketchPaint can B.

Personal protection:

Persons suffering from asthma, allergies or chronic or acute disorders of the respiratory tract, should not handle this product. Ensure adequate ventilation, which should be achieved by the use of local exhaust ventilation and good general ventilation. Do not eat, drink or smoke when using this product. Keep away from foodstuffs and beverages. Emergency showers.

Mouth and nose protection:

Adequate ventilation (ventilation factor > 1). Use only in well-ventilated areas. Respiratory protection in case of vapour/aerosol release. Combination filter for organic, inorganic, acid inorganic and alkaline gases/vapours (e.g. EN 14387 type ABEK, A1 or, if not available, EN 149 filter type A). When spraying: Self-contained breathing apparatus.

Skin and body:



Wear suitable protective work clothing and gloves. Remove contaminated clothing immediately. Wash thoroughly if skin comes into contact with the product. Store protective clothing separately. Emergency showers.

Hands:



Wash hands (and / or face) thoroughly before breaks and at the end of work. Wear protective gloves if skin contact may occur (EN 374). Do not rub eyes with dirty hands. For prolonged or repeated use: wear nitrile (0.4 mm layer thickness) or butyl (0.7 mm layer thickness) rubber gloves. Polyvinyl chloride (PVC) (0.7 mm layer thickness) and polyethylene laminate (PE laminate, 0.1 mm layer thickness) are unsuitable. Contaminated gloves should be replaced. Barrier creams may be applied to protect exposed skin. However, do not use these creams after exposure. On contact with a two-components product that just finished reacting, the use of chemical resistant gloves is recommended.

Eyes:



Safety goggles with side-shields (EN 166). Eye shower.



## SAFETY DATA

SHEET Edition: 7 November 2017  
Trade name: SketchPaint Can A  
Page: 10/17  
Version: 1.2

Measuring procedures: In order to establish compliance with an exposure limit and to establish that exposure is properly controlled, it may be necessary to determine the concentration of the substances in the inhalation zone or in the general workspace.

Environmental exposure control: Do not disperse product residues into the environment.

### SECTION 9: Physical and chemical properties.

#### 9.1. Information on basic physical and chemical properties

##### General information

##### Appearance

Form: Liquid.  
Colour: Clear, transparent.  
Odour: Neutral.  
Odour threshold: Not determined.  
pH-value: Not determined.  
Change in condition  
Melting point/melting range: Not determined.  
Initial boiling point and boiling range: Not determined.  
Flash point: > 100 °C.  
Flammability (solid, gas): Not determined.  
Auto-ignition temperature: Not determined.  
Explosive limits  
Lower: Not determined.  
Upper: Not determined.  
Vapour pressure: Not determined.  
Vapour density: Not determined.  
Relative density: 1.068 - 1.088 (water = 1).  
Evaporation rate: Not determined.  
Solubility in water: Freely soluble, reactive.  
Partition coefficient (n-octanol/water): Not determined.  
Viscosity  
Dynamic: Not determined.  
Kinematic: 57 - 63 KU at 25 °C (Stormer viscometer, ASTM Method D-562).  
Explosive properties: Not determined.  
Oxidising properties: Not determined.

9.2. Other information No data available.

### SECTION 10: Stability and reactivity.

10.1. Reactivity Contact with amines and alcohols causes exothermic reactions.

10.2. Chemical stability Stable under normal conditions.

Thermal decomposition/  
Conditions to avoid: No specific data available.



**SAFETY DATA**

SHEET Edition: 7 November 2017  
 Trade name: SketchPaint Can A  
 Page: 11/17  
 Version: 1.2

10.3. Possibility of hazardous reactions	May polymerize with many compounds e.g.: (strong) bases and amines. Reacts violently with (some) acids/bases.
10.4. Conditions to avoid	Contact with moisture (also from air). Temperatures above 90 °C. Avoid low temperatures (loss of quality).
10.5. Incompatible materials	Keep away from oxidants, strong bases and acids, protic solvents, amines and alcohols. The product reacts slowly with water, resulting in the production of CO <sub>2</sub> which may cause closed containers to burst.
10.6. Hazardous decomposition products	Unlikely at the recommended storage temperature and under normal conditions of use. In case of combustion: formation of toxic and corrosive gases/vapours: carbon monoxide, carbon dioxide, fume, nitrogen oxides, hydrogen cyanide.

**SECTION 11: Toxicological information.**

11.1. Information on toxicological effects  
 Acute toxicity from the components.  
 LD/LC50 values relevant for classification:

Product information: CAS#: 28182-81-2	Hexane, 1,6-diisocyanato-, homopolymer	
Oral	LD50	> 2500 mg/kg (rat female, OECD423)
Inhalation	LC50 (4 h)	0.39 mg/m <sup>3</sup> (rat female, OECD403)
Dermal	LD50	> 2000 mg/kg (rat, OECD402)
Product information: CAS#: 7087-68-5	Ethyl-diisopropylamine	
Oral	LD50	317 mg/kg (rat, 92/69/EEC - B.1)
Inhalation	LC50 (4 h)	-
Dermal	LD50	-
Product information: CAS#: 12788-93-1	Phosphoric acid, butyl ester	
Oral	LD50	959 mg/kg (rat, OECD401)
Inhalation	LC50 (4 h)	124 mg/m <sup>3</sup> (rat, OECD403)
Dermal	LD50	> 7000 mg/kg (rat, OECD402)
Product information: CAS#: 822-06-0	Hexamethylene diisocyanate/hexamethylene-1,6-diisocyanate	
Oral	LD50	959 mg/kg (rat, OECD401)
Inhalation	LC50 (4 h)	124 mg/m <sup>3</sup> (rat, OECD403)
Dermal	LD50	> 7000 mg/kg (rat, OECD402)

The following health hazard assessment is based on an assessment of the various ingredients in the product.

Primary irritant effect.

Effects on the eyes: Possible eye irritation. Reacts with aqueous humour.



**SAFETY DATA**

**SHEET Edition:** 7 November 2017  
**Trade name:** SketchPaint Can A  
**Page:** 12/17  
**Version:** 1.2

<b>Effects on the skin:</b>	Irritating. May cause sensitization by skin contact.
<b>Effect on the respiratory organs:</b>	May cause respiratory irritation.
<b>Chronic effects:</b>	Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL (=Occupational Exposure Limit). Repeated exposure may lead to permanent respiratory disability.
<b>Mutagenicity of reproductive cells: Reproductive and developmental toxicity:</b>	Not classified.  The substance contains isocyanate, showed mutagenic effects in various test systems with microorganisms and cell cultures; however, these results could not be confirmed in tests with mammals. The NOEL value of hexamethylene diisocyanate is set at 0.034 mg/m <sup>3</sup> .
<b>Sensitization:</b>	Contains isocyanate. May cause damage to organs through prolonged or repeated exposure if inhaled. For persons sensitized to isocyanates, exposure to levels even well below the PEL can lead to a severe allergic reaction.
<b>CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):</b>	Contains a small amount of N, N-diisopropylethylamine (CAS# 7087-68-5, < 1 %); under specific circumstances, ethyldiisopropylamine can form nitrosamines compounds which are carcinogenic in animal studies.
<b>Other information:</b>	No further relevant information available.

**SECTION 12: Ecological information.**

12.1. Toxicity  
 Ecotoxicity from the components.  
 Aquatic toxicity:

<b>Product information:</b> CAS#: 28182-81-2	Hexane, 1,6-diisocyanato-, homopolymer	
<b>Fish</b>	LL0 (96 h)	≥ 82.8 mg/l (Brachydanio rerio, EU Method C.1)
<b>Water flea</b>	EL50 (48 h)	127 mg/l (Daphnia magna, EU Method C.2)
<b>Algae</b>	EC50 (72 h)	370 mg/l (Desmodesmus subspicatus, EU Method C.3)
<b>Persistence and degradability</b>	ErC10 (72 h)	> 1000 mg/l <i>Desmodesmus subspicatus</i> , EU Method C.3)
	BOD28	1 % (EU C.4-E, unpublished)
	DT50	DT50 3 h (Photolysis) ((25°C, AOPWIN v1.92, internal evaluation)
<b>Bioaccumulative potential</b>	BCF	7.7 h (hyd., 23°C, ASTM D4666, internal evaluation)
<b>Mobility in soil</b>	Log Koc	3.2 (Fisch) (BCFWIN v. 2.17)
<b>Behaviour in purification plant</b>	EC50 (3 h)	7.8 (l) (PCKOC v1.66)
		3828 mg/l (activated sludge, OECD 209)
<b>Product information:</b> CAS#: 9046-01-9	polyoxyethylene tridecyl ether phosphate	
<b>Fish</b>	LC50 (96 h)	10 mg/l (Brachydanio rerio)
<b>Water flea</b>	EC0 (48 h)	-
<b>Algae</b>	EC50 (72 h)	-
<b>Behaviour in purification plant</b>	EC20 (30 m)	> 1000 mg/l (activated sludge, DIN EN ISO 8192)



**SAFETY DATA**

SHEET Edition: 7 November 2017  
 Trade name: SketchPaint Can A  
 Page: 13/17  
 Version: 1.2

Product information: CAS#: 7087-68-5	Ethyl-diisopropylamine	
Fish	LC50 (96 h)	-
Water flea	EC0 (48 h)	74.3 mg/l (Daphnia magna, 79/831/EEC)
Algae	EC50 (72 h)	-
Bacteria	EC50	-
Product information: CAS#: 12788-93-1	Phosphoric acid, butyl ester	
Fish	LC50 (96 h)	> 100 mg/l (Oncorhynchus mykiss)
Water flea	EC0 (48 h)	> 100 mg/l (Daphnia magna, OECD202)
Algae	EC50 (72 h)	-
Behaviour in purification plant	EC50	> 100 mg/l (activated sludge)
Product information: CAS#: 822-06-0	Hexamethylene diisocyanate/hexamethylene-1,6-diisocyanate	
Fish	LC0 (96 h)	≥ 82.8 mg/l (Danio rerio, EU Method C.1)
Water flea	EC0 (48 h)	≥ 89.1 mg/l (Daphnia magna, EU Method C.2)
Algae	EC50 (72 h)	> 77.4 mg/l (Desmodesmus subspicatus, EU Method C.3)
Bacteria	EC50 (3 h)	842 mg/l (activated sludge, similar to OECD209)
The following ecological risk assessment is based on an assessment of the various ingredients in the product.		
12.2. Persistence and degradability	Contains isocyanate, of which no biodegradation was observed under test conditions.	
12.3. Bioaccumulative potential	Significant accumulation in organisms is not to be expected.	
12.4. Mobility in soil	The product has limited solubility in water. The product reacts with water to form insoluble polyurea.	
Further ecological information. General information:	-	
12.5. Results of PBT and vPvB assessment	The product does not meet all of the assessment criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.	
12.6. Other adverse effects	Not dangerous for the ozone layer.	

**SECTION 13: Disposal considerations.**

13.1. Waste treatment methods

Product waste:

Neutralise, see section 6. May be brought to a supervised incineration plant in compliance with local regulations. The generation of waste should be avoided or minimised wherever possible. If this is not possible, destroy in an approved incineration facility, where flue gases and other toxic combustion products are washed and neutralised. Waste, even small quantities, should never be poured down drains of



## SAFETY DATA

SHEET Edition: 7 November 2017  
Trade name: SketchPaint Can A  
Page: 14/17  
Version: 1.2

Eural code for waste:	discharged in surface water. 08 04 09*. WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS, wastes from MFSU of adhesives and sealants (including waterproofing products) ; wastes from adhesives and sealants containing organic solvents or other dangerous substances. Classified as hazardous waste. Depending on branch of industry and production process, also other EURAL codes may be applicable. Hazardous waste according to Directive 2008/98/EC.
Uncleaned packaging. Recommendation:	Disposal must be made according to official regulations. Empty the packaging with care. Do not contaminate soil, water or environment with the waste container. Comply with local regulations with regard to the recovery or disposal of waste.
Eural code for packaging:	08 05 01*. WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS not otherwise specified in 08; waste isocyanates. Classified as hazardous waste.

## SECTION 14: Transport information.

### Land transport ADR/RID (cross-border).

ADR/GGVSEB class: -  
Hazard identification number: -  
UN number: -  
Packing group: -  
Label: -  
Special marking: -  
UN proper shipping name: -  
Tunnel restriction code: -  
Note: Not a dangerous good according to the transport regulations.

### Inland shipping ADN/ADR.

ADN/R-class: -  
UN number: -  
Environmental hazards: -

### Maritime transport IMDG.

IMDG-class: -  
UN number: -  
Label: -  
Packing group: -  
Maximum quantity: -  
EMS number: -  
Stowage and segregation: -



## SAFETY DATA

SHEET Edition: 7 November 2017  
Trade name: SketchPaint Can A  
Page: 15/17  
Version: 1.2

Marine pollutant:	-
Proper shipping name:	-
Air transport ICAO-TI and IATA-DGR.	
ICAO/IATA class:	-
UN number:	-
Label:	-
Packing group:	-
Proper shipping name:	-
14.1. UN number	Void.
14.2. UN proper shipping name	Void.
14.3. Transport hazard class(es)	Void.
14.4. Packing group	Void.
14.5. Environmental hazards	Void.
14.6. Special precautions for user	None.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Void.

## SECTION 15: Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
National regulations: -

EU regulations and directives which affect this mixture (not yet directly or indirectly mentioned):

Directive 89/686/EEC	Personal protective equipment (is to be replaced from 21 April 2018 by regulation (EU) 2016/425).
Directive 94/33/EC	Protection of young people at work.
Directive 98/24/EC	Risks related to chemical agents at work.
Regulation (EC) 2009/552	Annex XVII to Regulation 1907/2009; diisocyanates from MDI for consumers (supplement to Regulation 2013/126).
Regulation (EC) 1907/2006	Annex XV restriction report, proposal for a restriction (diisocyanates), ECHA / BAuA, 06 October 2016.
Regulation (EC) 2008/1272	On classification, labelling and packaging of substances and mixtures.
Regulation (EU) 2015/830	Commission regulation of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment A chemical safety assessment has not been carried out.

## SECTION 16: Other information.



## SAFETY DATA

SHEET Edition: 7 November 2017  
Trade name: SketchPaint Can A  
Page: 16/17  
Version: 1.2

List of relevant H- and EUH-phrase(s) referred to under headings 2 and 3:

H225 - Highly flammable liquid and vapour.  
H302 - Harmful if swallowed.  
H314 - Causes severe skin burns and eye damage.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H319 - Causes serious eye irritation.  
H330 - Fatal if inhaled.  
H332 - Harmful if inhaled.  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 - May cause respiratory irritation.  
H411 - Toxic to aquatic life with long lasting effects.  
H412 - Harmful to aquatic life with long lasting effects.  
EUH204 - Contains isocyanates. May produce an allergic reaction.  
Aquatic Chronic - Hazardous to the aquatic environment, chronic.  
Acute Tox. - Acute toxicity.  
Eye Dam. - Serious eye damage.  
Eye Irrit. - Serious eye irritation.  
Flam. Liq. - Flammable liquid.  
Skin Corr. - Skin corrosion.  
Skin Irrit. - Skin irritation.  
Skin Sens. - Skin sensitization.  
STOT SE - Specific target organ toxicity - single exposure.

Document history: Printed on: 19 February 2018.  
Previous edition: 05.04.2014, version 1.1.  
Version: 1.2.  
Modification: According to safety data sheet legislation.

Information source: -

Classification according to Regulation (EC) No 1272/2008: Classification of the mixture based on the standard calculation method.

The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the product's properties. It is the obligation of the user to use this product with care and to act in consideration of the applicable laws and legislation.

SketchPaint can A is a trademark of MagPaint Europe B.V..

### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)



**Producer:** MagPaint Europe B.V., Riezenweg 2, NL – 7071 PR Uift  
**Distributor:** SIA "Krāsu serviss", Vienības gatve 93, Rīga, Latvija, LV-1058  
Tel.+ 371 669 39 669, info@krasas.lv, www.krasas.lv



## SAFETY DATA

SHEET Edition: 7 November 2017  
Trade name: SketchPaint Can A  
Page: 17/17  
Version: 1.2

IMDG:	International Maritime Code for Dangerous Goods
IATA:	International Air Transport Association
IATA-DGR:	Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO:	International Civil Aviation Organization
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO)
P:	Marine Pollutant
GHS:	Globally Harmonized System of Classification and Labelling of Chemicals
CAS:	Chemical Abstracts Service (division of the American Chemical Society)
EC50:	Half maximal effective concentration
LC50:	Lethal concentration, 50 percent
LD50:	Lethal dose, 50 percent
OEL:	Occupational Exposure Limit
NOEC:	No Observed Effect Concentration
vPvB:	Very Persistent and Very Bioaccumulative
PBT	Persistent, Bioaccumulative and Toxic substance
EWC:	European Waste Catalogue
TWA:	Time-Weighted Average, limit value associated with the MAC value
DNEL:	Derived No-Effect Level
DMEL:	Derived Minimal Effect Level
PNEC:	Predicted No-Effect Concentration

## SAFETY DATA

SHEET Edition: 12 November 2017  
Trade name: SketchPaint White Matt Can B  
Page: 1/13  
Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking.

#### 1.1. Product identifier

Trade name: **SketchPaint White Matt Can B**  
Synonyms: Whiteboard paint – Dry-erase paint

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

A smooth surface treated with SketchPaint is writable and erasable with most whiteboard markers.  
Component of a two-component product.  
Product category: PROC19 (Hand-mixing),  
PROC10 (Roller application or brushing).

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer/supplier: MagPaint Europe B.V.  
Riezenweg 2  
7071 PR Uift  
THE NETHERLANDS  
Tel.: +31 (0) 315 38 64 73  
Email: info@magpaint.com  
Website: www.magpaint.com

#### Further information obtainable from:

Contact person: Mike Poorthuis  
Tel.: +31 (0) 315 38 64 73  
Email: info@magpaint.com  
Working hours (business days): 09h00-17h00

#### 1.4. Emergency telephone number

The Netherlands: Nationaal Vergifingen Informatie  
Centrum (NVIC): +31 (0) 30 247 88 88  
Belgium: Belgian Poison Centre: +32 (0) 70 245 245  
United Kingdom: UWIC: +44 (0) 29 204 16388

### SECTION 2: Hazards identification.

#### 2.1. Classification of the substance or mixture

Classification in accordance with Regulation (EC) no 1272/2008  
Void.

#### 2.2. Label elements

Hazard pictograms: -  
Signal word: -  
Hazard statements: -  
Precautions: -

Hazard-determining components for labelling: -

2.3. Other hazards -



## SAFETY DATA

SHEET Edition: 12 November 2017  
Trade name: SketchPaint White Matt Can B  
Page: 2/13  
Version: 1.1

### Results of PBT and vPvB assessment

PBT: No.  
vPvB: No.

## SECTION 3: Composition/information on ingredients.

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

Chemical description: Preparation comprising the following component(s) and (other) unclassified components.

#### Titanium dioxide

CAS#: 13463-67-7  
EC#: 236-675-5  
Index#: -  
REACH reg.#: 01-2119489379-17  
Content (W/W): 20 - 30 %  
Danger, 1272/2008/EC: -

#### Silicon dioxide (contains traces of CAS # 112945-52-5), amorphous (silica)

CAS#: 7631-86-9  
EC#: 231-545-4  
Index#: -  
REACH reg.#: 01-2119379499-16  
Content (W/W): 1 - 5 %  
Danger, 1272/2008/EC: -

#### Poly(oxy-1; 2-ethanedilyl), $\alpha$ -methyl- $\infty$ -[(4, 4, 5, 5, 6, 6, 7, 7, 8, 8, 9, 9-tridecafluoro-2-hydroxynonyl)oxy]

CAS#: 1227060-33-4  
EC#: -  
Index#: -  
REACH reg.#: -  
Content (W/W): 1 - 3 %  
Danger, 1272/2008/EC: Acute Tox. 4; H302 - Aquatic Chronic 3; H412

Full text of H- and EUH-phrase(s): See section 16.

## SECTION 4: First aid measures.

### 4.1. Description of first aid measures

General information: If in doubt or if symptoms persist, seek medical attention.

Eye contact: Mild irritation. Flush eyes thoroughly with water (for at least 10 minutes) while holding eyelids open. Then immediately consult a physician/ophthalmologist.

Skin contact: Remove mechanically, wash with plenty of soap and water, liberally apply skin cream to clean skin. Consult a physician in case of persistent pain or redness.

Ingestion: Rinse mouth with water and give two glasses of water to drink



## SAFETY DATA

SHEET Edition: 12 November 2017  
Trade name: SketchPaint White Matt Can B  
Page: 3/13  
Version: 1.1

If aerosol or vapour is inhaled in high concentrations:	(Never make an unconscious person drink fluids because of risk of suffocation). Do NOT induce vomiting. If symptoms develop: Get medical advice/attention.  Take the person into the fresh air, keep him warm, let him rest. If symptoms occur (e.g. breathing difficulties) medical attention is required.
4.2. Most important symptoms and effects, both acute and delayed	
Inhalation:	No known significant effects or critical hazards.
Skin contact:	By mechanical damage (particles): redness.
Eye contact:	By mechanical damage (particles): irritation, redness and pain.
Ingestion:	Irritation.
4.3. Indication of any immediate medical attention and special treatment needed	
Further medical treatment:	Symptomatic treatment and supportive therapy as prescribed.

## SECTION 5: Firefighting measures.

5.1. Extinguishing media	
Suitable extinguishing media:	Use CO <sub>2</sub> , ABC powder. Fight larger fires with water spray.
Unsuitable extinguishing media for safety reasons:	Direct water stream may be ineffective.
5.2. Special hazards arising from the substance or mixture	
Special hazards:	Not classified as flammable. In case of fire, hazardous and toxic vapours may be released. Possible decomposition products are: carbon monoxide and carbon dioxide. The reacted product can contribute to the fire.
5.3. Advice for fire-fighters	
Protection of fire-fighters:	For fire-fighters, mouth and nose protection with independent air supply (breathing apparatus) and full (chemical) protective clothing are mandatory. Use qualified personnel who are well aware of the dangers of this product. After use, clean the equipment thoroughly (shower, clean clothing thoroughly and check suitability).
Additional information:	If closed containers are exposed to fire, keep cool with water.

## SECTION 6: Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures	
	Wear appropriate personal protective equipment, including safety glasses, personal protective clothing and chemical resistant gloves when cleaning up major spillages. Ventilate the area.
6.2. Environmental precautions	
	Prevent product from entering sewers or surface water. If significant quantities are being released in the environment, inform the local authorities. Do not allow to enter the soil or subsoil.



**SAFETY DATA**

SHEET Edition: 12 November 2017  
 Trade name: SketchPaint White Matt Can B  
 Page: 4/13  
 Version: 1.1

6.3. Methods and material for containment and cleaning up	Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. Wash the spillage area clean with water and detergent.
6.4. Reference to other sections	Information regarding safe handling – see section 7. Information regarding personal protective equipment – see section 8. Information regarding disposal – see section 13.

<b>SECTION 7: Handling and storage.</b>	
7.1. Precautions for safe handling Handling:	When handling observe the usual precautionary measures for chemicals. Do not breathe vapour. Workers should wash hands and face before eating, drinking and smoking. Material contains solid components as filler; mix before use. Part of two-component product. Do not dilute or mix with other (paint) products.
7.2. Conditions for safe storage, including any incompatibilities Storage:	Keep container tightly closed in a cool, well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from direct sunlight. Avoid moisture from entering by keeping the containers tightly closed when not in use.
Requirements to be met by storerooms and receptacles:	Preferably keep in the original packaging.
Packaging material, suitable:	Original packaging. Closed, coated tin or plastic can.
Packaging material, unsuitable:	Zinc, aluminium.
Information about storage in one common storage facility:	Keep away from oxidants, strong bases and acids.
Further information about storage conditions:	Recommended storage temperature 1 - 49 °C.
7.3. Specific end use(s)	No further relevant information available.

<b>SECTION 8: Exposure controls/personal protection.</b>		
8.1. Control parameters		
Ingredients with limit values that require monitoring at the workplace:		
Product information: CAS#: 13463-67-7	Titanium dioxide	
TWA 8 h	mg/m <sup>3</sup> (ppm)	10 (-) formerly Dutch value, France, England, Belgium, Spain 6 (-) Denmark 5 (-) Norway, Austria, Sweden 3 (-) Switzerland
TWA 15 minutes		10 (-) Austria



**SAFETY DATA**

SHEET Edition:

12 November 2017

Trade name:

SketchPaint White Matt Can B

Page:

5/13

Version:

1.1

Dangerous ingredients with DN(M)EL:				
Product information:	Exposure	Value	Unit	Population / Effects
Titanium dioxide CAS#: 13463-67-7				
DN(M)EL	Short-term dermal	-	mg/kg bw/day	Workers Local
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	Workers Local
DN(M)EL	Short-term dermal	-	mg/kg bw/day	Workers Systemic
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	Workers Systemic
DN(M)EL	Long-term dermal	-	mg/kg bw/day	Workers Local
DN(M)EL	Long-term inhalation	10	mg/m <sup>3</sup>	Workers Local
DN(M)EL	Long-term dermal	-	mg/kg bw/day	Workers Systemic
DN(M)EL	Long-term inhalation	-	mg/m <sup>3</sup>	Workers Systemic
DN(M)EL	Short-term dermal	-	mg/kg bw/day	General population Local
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	General population Local
DN(M)EL	Short-term dermal	-	mg/kg bw/day	General population Systemic
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	General population Systemic
DN(M)EL	Short-term Oral	-	mg/kg bw/day	General population Systemic
DN(M)EL	Long-term dermal	-	mg/kg bw/day	General population Systemic
DN(M)EL	Long-term inhalation	-	mg/m <sup>3</sup>	General population Systemic
DN(M)EL	Long-term oral	700	mg/kg bw/day	General population Systemic
DN(M)EL	Long-term dermal	-	mg/kg bw/day	General population Local
DN(M)EL	Long-term inhalation	10	mg/m <sup>3</sup>	General population Local
Dangerous ingredients with DN(M)EL:				
Product information:	Exposure	Value	Unit	Population / Effects
Silicon dioxide CAS#: 7631-86-9				



**SAFETY DATA**

SHEET Edition:

12 November 2017

Trade name:

SketchPaint White Matt Can B

Page:

6/13

Version:

1.1

DN(M)EL	Short-term dermal	-	mg/kg bw/day	Workers Local
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	Workers Local
DN(M)EL	Short-term dermal	-	mg/kg bw/day	Workers Systemic
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	Workers Systemic
DN(M)EL	Long-term dermal	-	mg/kg bw/day	Workers Local
DN(M)EL	Long-term inhalation	-	mg/m <sup>3</sup>	Workers Local
DN(M)EL	Long-term dermal	-	mg/kg bw/day	Workers Systemic
DN(M)EL	Long-term inhalation	4	mg/m <sup>3</sup>	Workers Systemic
DN(M)EL	Short-term dermal	-	mg/kg bw/day	General population Local
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	General population Local
DN(M)EL	Short-term dermal	-	mg/kg bw/day	General population Systemic
DN(M)EL	Short-term inhalation	-	mg/m <sup>3</sup>	General population Systemic
DN(M)EL	Short-term Oral	-	mg/kg bw/day	General population Systemic
DN(M)EL	Long-term dermal	-	mg/kg bw/day	General population Systemic
DN(M)EL	Long-term inhalation	-	mg/m <sup>3</sup>	General population Systemic
DN(M)EL	Long-term oral	-	mg/kg bw/day	General population Systemic
DN(M)EL	Long-term dermal	-	mg/kg bw/day	General population Local
DN(M)EL	Long-term inhalation	-	mg/m <sup>3</sup>	General population Local

Dangerous ingredients with PNEC:			
Product information:	Value	Unit	Compartment
Titanium dioxide CAS#: 13463-67-7			
PNEC	0.127	mg/l	Fresh water
PNEC	1	mg/l	Marine water
PNEC	0.61	mg/l	Intermittent releases
PNEC	100	mg/l	STP (sewage treatment plant)
PNEC	1000	mg/kg dwt	Sediment fresh water



**SAFETY DATA**

SHEET Edition: 12 November 2017  
 Trade name: SketchPaint White Matt Can B  
 Page: 7/13  
 Version: 1.1

PNEC	100	mg/kg dwt	Sediment marine water
PNEC	100	mg/kg wwt	Soil
PNEC	1667	mg/l	Oral


8.2. Exposure controls

Note: Material is part of a two-component system. For exposure controls, see also section 8 of the safety data sheet of SketchPaint can A.


Personal protection: Do not smoke, eat or drink whilst working. Wear suitable protective clothing (preferably cotton).

Mouth and nose protection: Required in insufficiently ventilated working areas. Wear suitable autonomous breathing apparatus in case of insufficient ventilation or if required by company regulations.

Skin and body: Wear suitable protective clothing (overalls, preferably thick cotton or disposable protective suit), gloves and eye / face protection. Wash hands before breaks and at the end of work. Remove immediately all contaminated clothing. Store working clothes separately. Do not use solvents or thinner.

 Hands: Wash hands (and / or face) thoroughly before breaks and at the end of work. Wear protective gloves if skin contact may occur (EN 374). Do not rub eyes with dirty hands. For prolonged or repeated use: wear nitrile (0.4 mm layer thickness) or butyl (0.7 mm layer thickness) rubber gloves. Polyvinyl chloride (PVC) (0.7 mm layer thickness) and polyethylene laminate (PE laminate, 0.1 mm layer thickness) are unsuitable. Contaminated gloves should be replaced. Barrier creams may be applied to protect exposed skin. However, do not use these creams after exposure. On contact with a two-components product that just finished reacting, the use of chemical resistant gloves is recommended.

Eyes: Safety goggles with side-shields (EN 166). Eye shower.

 Measuring procedures: In order to establish compliance with an exposure limit and to establish that exposure is properly controlled, it may be necessary to determine the concentration of the substances in the inhalation zone or in the general workspace.

Environmental exposure control: Do not disperse product residues into the environment.

**SECTION 9: Physical and chemical properties.**

9.1. Information on basic physical and chemical properties

General information

Appearance

Form: Liquid.  
 Colour: White.  
 Odour: Slightly irritant.  
 Odour threshold: Not determined.  
 pH-value: 7.4 - 7.7.





## SAFETY DATA

SHEET Edition: 12 November 2017  
Trade name: SketchPaint White Matt Can B  
Page: 8/13  
Version: 1.1

Change in condition	
Melting point/melting range:	Not determined.
Initial boiling point and boiling range:	Not determined.
Flash point:	> 100 °C.
Flammability (solid, gas):	Not determined.
Auto-ignition temperature:	Not determined.
Explosive limits	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Vapour density:	Not determined.
Relative density:	1.28 - 1.32 (water = 1).
Evaporation rate:	Not determined.
Solubility in water:	Freely soluble.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity	
Dynamic:	Not determined.
Kinematic:	80 - 85 KU at 25 °C (Stormer viscometer, ASTM Method D-562).
Explosive properties:	Not determined.
Oxidising properties:	Not determined.
9.2. Other information	No data available.

## SECTION 10: Stability and reactivity.

10.1. Reactivity	No specific data available.
10.2. Chemical stability	Stable under normal conditions.
Thermal decomposition/ Conditions to avoid:	No specific data available.
10.3. Possibility of hazardous reactions	No specific data available.
10.4. Conditions to avoid	Avoid high and low temperatures (loss of quality).
10.5. Incompatible materials	Keep away from oxidants, strong bases and acids. Reacts violently with lithium, aluminium, calcium, magnesium, potassium, sodium and zinc.
10.6. Hazardous decomposition products	Unlikely at the recommended storage temperature and under normal conditions of use. In case of combustion: formation of toxic and corrosive gases/vapours: carbon monoxide, carbon dioxide, fume.

## SECTION 11: Toxicological information.

11.1. Information on toxicological effects	Acute toxicity from the components.
--	-------------------------------------



**SAFETY DATA**

SHEET Edition: 12 November 2017  
 Trade name: SketchPaint White Matt Can B  
 Page: 9/13  
 Version: 1.1

LD/LC50 values relevant for classification:

Product information: CAS#: 13463-67-7	Titanium dioxide	
Oral	LD50	> 5000 mg/kg (rat female, OECD425)
Inhalation	LC50 (4 h)	6.82 mg/m <sup>3</sup> (rat male)
Dermal	LD50	-
Product information: CAS#: 7631-86-9	Silicon dioxide	
Oral	LD50	> 10000 mg/kg (rat)
Inhalation	LC50 (4 h)	0.139 mg/m <sup>3</sup> (rat male)
Dermal	LD50	> 5000 mg/kg (rabbit)
Product information: CAS#: 1227060-33-4 (source supplier)	Poly(oxy-1; 2-ethanedilyl), α-methyl-∞-[(4, 4, 5, 5, 6, 6, 7, 7, 8, 8, 9, 9-tridecafluoro-2-hydroxynonyl)oxy]	
Oral	LD50	550 mg/kg (rat)
Inhalation	LC50 (4 h)	5.9 mg/l (rat male)
Dermal	LD50	> 5000 mg/kg (rat)

The following health risk assessment is based on an assessment of the various ingredients in the product.

Primary irritant effect.

Effects on the eyes: By mechanical damage (particles): irritation, redness and pain.  
 Effects on the skin: By mechanical damage (particles): redness.

Chronic effects: Not classified.

Mutagenicity of reproductive cells: Not classified.

Reproductive and developmental toxicity: Not classified.

Sensitisation: Not classified.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction): Not classified.

Other information: No further relevant information available.

**SECTION 12: Ecological information.**

12.1. Toxicity

Ecotoxicity from the components.

Aquatic toxicity:

Product information: CAS#: 13463-67-7	Titanium dioxide	
Fish	LC50 (96 h)	> 10,000 mg/l (Cyprinodon variegatus, OECD 203)
Water flea	EL50 (48 h)	> 100 mg/l (Daphnia magna, OECD 202)
Algae	EC50 (72 h)	61 mg/l (Pseudokirchnerella subcapitata, EPA-600/9-78-018)
Product information: CAS#: 7631-86-9	Silicon dioxide	
Fish	LC50 (96 h)	> 10000 mg/l (brachydanio rerio, OECD 203)



**SAFETY DATA**

SHEET Edition: 12 November 2017  
 Trade name: SketchPaint White Matt Can B  
 Page: 10/13  
 Version: 1.1

Water flea	EL50 (48 h)	> 10000 mg/l (daphnia magna, OECD 202)
Algae	EC50 (72 h)	-
Product information: CAS#: 1227060-33-4 (source supplier)	Poly(oxy-1; 2-ethanedilyl), α-methyl-∞-[(4, 4, 5, 5, 6, 6, 7, 7, 8, 8, 9, 9-tridecafluoro-2-hydroxyonyl)oxy]	
Fish	LC50 (96 h)	36.7 mg/l (oncorhynchus mykiss)
Water flea	EC50 (48 h)	28.8 mg/l (daphnia magna)
Algae	ErC50 (72 h)	88.3 mg/l (pseudokirchnerella subcapitata)
The following ecological risk assessment is based on an assessment of the various ingredients in the product.		
12.2. Persistence and degradability	Contains inorganic components.	
12.3. Bioaccumulative potential	Significant accumulation in organisms is not to be expected.	
12.4. Mobility in soil	The product is (partially) soluble in water.	
Further ecological information. General information:	-	
12.5. Results of PBT and vPvB assessment	The product does not meet all of the assessment criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.	
12.6. Other adverse effects	Not dangerous for the ozone layer.	

**SECTION 13: Disposal considerations.**

13.1. Waste treatment methods	
Product waste:	May be brought to a supervised incineration plant in compliance with local regulations. The generation of waste should be avoided or minimised wherever possible. If this is not possible, destroy in an approved incineration facility, where flue gases and other toxic combustion products are washed and neutralised. Waste, even small quantities, should never be poured down drains or discharged in surface water.
Eural code for waste:	08 01 12. WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS, wastes from MFSU of adhesives and sealants (including waterproofing products); waste paint and varnish other than those mentioned in 08 01 11. Depending on branch of industry and production process, also other EURAL codes may be applicable.
Uncleaned packaging. Recommendation:	Disposal must be made according to official regulations. Empty the packaging with care. Do not contaminate soil, water or



**SAFETY DATA**

SHEET Edition: 12 November 2017  
Trade name: SketchPaint White Matt Can B  
Page: 11/13  
Version: 1.1

Eural code for packaging:	environment with the waste container. Comply with local regulations with regard to the recovery or disposal of waste. 20 01 27*. MUNICIPAL WASTES AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES INCLUDING SEPARATELY COLLECTED FRACTIONS, paints, inks, adhesives and resins containing dangerous substances. Classified as hazardous waste.
---------------------------	--

**SECTION 14: Transport information.**

Land transport ADR/RID (cross-border).  
ADR/GGVSEB class: -  
Hazard identification number: -  
UN number: -  
Packing group: -  
Label: -  
Special marking: -  
UN proper shipping name: -  
Tunnel restriction code: -  
Note: Not a dangerous good according to the transport regulations.

Inland shipping ADN/ADR.  
ADN/R-class: -  
UN number: -  
Environmental hazards: -

Maritime transport IMDG.  
IMDG-class: -  
UN number: -  
Label: -  
Packing group: -  
Maximum quantity: -  
EMS number: -  
Stowage and segregation: -  
Marine pollutant: -  
Proper shipping name: -

Air transport ICAO-TI and IATA-DGR.  
ICAO/IATA class: -  
UN number: -  
Label: -  
Packing group: -  
Proper shipping name: -

14.1. UN number Void.  
14.2. UN proper shipping name Void.  
14.3. Transport hazard class(es) Void.



## SAFETY DATA

SHEET Edition: 12 November 2017  
Trade name: SketchPaint White Matt Can B  
Page: 12/13  
Version: 1.1

14.4. Packing group	Void.
14.5. Environmental hazards	Void.
14.6. Special precautions for user	None.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Void.

## SECTION 15: Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
National regulations: -

EU regulations and directives which affect this mixture (not yet directly or indirectly mentioned):

Directive 89/686/EEC

Personal protective equipment (is to be replaced from 21 April 2018 by regulation (EU) 2016/425).

Directive 98/24/EC

Risks related to chemical agents at work.

Directive 2004/42/EC

On the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes.

VOC content: nil/low.

RAC

Committee for Risk Assessment RAC Opinion proposing harmonised classification and labelling at EU level of Titanium dioxide (14 September 2017, CLH-O-0000001412-86-163/F, RAC opinion Carc.2; H351 (inhalation)).

Regulation (EC) 2008/1272

On classification, labelling and packaging of substances and mixtures.

Regulation (EU) 2015/830

Commission regulation of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment A chemical safety assessment has not been carried out.

## SECTION 16. Other information.

List of relevant H- and EUH-phrase(s) referred to under headings 2 and 3:

H302 - Harmful if swallowed.

H412 - Harmful to aquatic life with long lasting effects.

Acute Tox. - Acute toxicity.

Aquatic Chronic - Hazardous to the aquatic environment, chronic.

Document history:

Printed on: 19 February 2018.

Previous edition: 5 April 2014, version 1.0.

Version: 1.1.

Modification: According to safety data sheet legislation.



## SAFETY DATA

SHEET Edition: 12 November 2017  
Trade name: SketchPaint White Matt Can B  
Page: 13/13  
Version: 1.1

Information source: -

Classification according to Regulation  
(EC) No 1272/2008: -

The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the product's properties. It is the obligation of the user to use this product with care and to act in consideration of the applicable laws and legislation.

SketchPaint White matt can B is a trademark of MagPaint Europe B.V.

### Abbreviations and acronyms:

ADR:	Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID:	Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG:	International Maritime Code for Dangerous Goods
IATA:	International Air Transport Association
IATA-DGR:	Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO:	International Civil Aviation Organization
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO)
P:	Marine Pollutant
GHS:	Globally Harmonized System of Classification and Labelling of Chemicals
CAS:	Chemical Abstracts Service (division of the American Chemical Society)
EC50:	Half maximal effective concentration
LC50:	Lethal concentration, 50 percent
LD50:	Lethal dose, 50 percent
OEL:	Occupational Exposure Limit
NOEC:	No Observed Effect Concentration
vPvB:	Very Persistent and Very Bioaccumulative
PBT:	Persistent, Bioaccumulative and Toxic substance
EWC:	European Waste Catalogue
TWA:	Time-Weighted Average, limit value associated with the MAC value
DNEL:	Derived No-Effect Level
DMEL:	Derived Minimal Effect Level
PNEC:	Predicted No-Effect Concentration