

Outdoor Primer Classic



TECHNICAL PRODUCT DATA SHEET

2022-10-26

Page 1/2

Product description:

Outdoor Primer Classicis a matte, traditional alkyd-based primer for exterior wooden surfaces. The paint has good penetration characteristics, and excellent adhesion and richness. The primer is suitable for all exterior wood paints.

Outdoor Primer Classic is produced in Sweden.

TECHNICAL DATA:

Area of application Outdoors

Binder Alkyd Volume Solids 46%

Density 1,29 kg/l
Gloss Fully matt

Washability Class 1 (EN 13300)
Thinner/Cleaning White spirit/Naphtha

Material consumption 4–7 m²/L sawn wood, 7–10 m²/L planed wood

Temperature at painting Minimum +5°C

Tools for painting Brush, roller and sprayer

Dust dry 4 h

Re-paintable 16-24 h

Completely dry Several days

Colour White

Flammability 3

VOC category (Cat. A/d): 300 g/l (2010)

Hagmans Nordic AB
Box 112, 511 10 Fritsla
Telefon: +4632018900
order@hagmansnordic.com

Version: 2022-10-26 12:34



Outdoor Primer Classic



TECHNICAL PRODUCT DATA SHEET

2022-10-26

Page 2/2

How to use

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint. The air and surface temperature is also important for the end result. Do not paint if it is below +5°C. The surface must be clean, dry and firm. Brush or scrape off loose old paint and/or porous and degraded wood. Wash previously painted surfaces with appropriate cleaner. Rinse with water and let dry.

Before priming it is preferable to use Grundolja Classic, especially when it comes to end grains and wood joints.

Painting

Apply one or two coats. The first layer – diluted with 5% Naphta – can be used for more intense penetration. Apply preferably several thin coats – with a day or two to dry in between – then a few thicker coats. Wood not previous treated, two coats is to recommend. Avoid painting on warm and sunlit surfaces. When the primer is completely dry, use one of our top coats for outdoors, for instance Storm, Solid or Titan.

Post-painting

Wipe off the tools thoroughly before cleaning with white spirit. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

Hagmans Nordic AB Box 112, 511 10 Fritsla Telefon: +4632018900 order@hagmansnordic.com Version: 2022-10-26 12:34