

Dustbinder

Hagmans Dammbindning 1K (1-C dust binder) is a colour less, water-borne acrylic-based dust binder/primer for cement and other absorbent mineral substrates.

Hagmans Dammbindning 1K is primarily intended for dust binding in cement floors and walls where it also strengthens the surface. It can also be used as a primer when painting with Golvfärg 1K (1-C floor paint) on clean cement outdoors, such as balconies or stairs for better adhesion and to further strengthen the surface.

| | |
|------------------------------|----------------------------------|
| Basic material: | Acrylic dispersion |
| Density: | 1.01 |
| Material consumption: | 6-8m ² /l |
| Drying time: | approx. 1 hour (20°C, 50% RH) |
| Diffusion properties: | Diffusion opens |
| Colour: | Transparent |
| Packaging: | 1, 4, 10, and 25 liters |
| Pot life: | 2 years |

Preparation: Turn off the floor heating before painting. New cement must be cured for a least one week, be dry and free of dirt, oil and similar. The cement skin must be removed, such as by grinding or with an acid wash.

Instructions for use: Apply in a layer with a paintbrush, roller or low pressure spray gun. Make sure ventilation is good. If the humidity levels exceed 85% a matt, streaked surface may result. Paintbrushes and other equipment can be cleaned with water. Do not treat surfaces with a temperature lower than 5°C.



| | |
|---|--|
| CE | |
| Hagmans Kemi AB Box 112 51110 Fritsla 13 | |
| EN 1504-2 38501-002 | |
| Product for the protection of concrete surfaces Coating | |
| Reaction to fire Permeability to water vapour Capillary absorption and permeability to water Adhesion strength | B _{fl} -s1 Class I w < 0,1 kg/m ² h ^{0,5} >2,0 N/mm ² |