

Barrier Primer

Product description

Hagmans Spärrgrund is a waterborne primer for wood.

Areas of use:

For use indoors on untreated or previously treated wood to reduce the risk of discolouration from twigs, lignin, old yellowed wood, etc. Can be coated with waterborne paint, e.g. Hagmans Golvfärg EP-V (floor paint) or Hagmans Golvfärg 1K (1-compound floor paint)

Technical information:

Basic material: Acrylate

Density: approx. 1.2 kg/l

Dry content: weight: 48 % volume: 38 %

Gloss: Semi-matte

Material

consumption: approx. 8 m²/l

Lowest

working temp. +10 °C

Dust dry: 1 hour (at 20 °C and 60 % RF)

Coatable: 8 hours (at 20 °C and 60 % RF)

Cleaning tools: Water

Pot life: 2 years. Store frost-free and tightly sealed.

Preparation:

The substrate must be clean and dry. Previously painted surfaces must be washed and ground matte.

Instructions for use (incl. application):

Apply with a roller or paintbrush in 1-2 layers, depending on risk for penetration. Always apply two layers over twigs on untreated wood or if the substrate is strongly discoloured. Note that primed surfaces must dry for at least 8 hours between each application. The first layer may become discoloured on strongly discoloured substrates. This becomes fixed when the paint

layer has dried, so the risk for further penetration is small.

Packaging:

31301	1L
31302	4L
31304	10L

Colours:

White

Other information:

Note! Twig penetration is a natural phenomenon that in certain cases can occur despite treatment.

