


ADLER Floor-Start

42110



Product description	Water-thinnable 1-K-priming coat on PUR-Acrylate-dispersion basis for hard- and softwood, isolates wood extractives on tannin containing wood. Low raising of wood grain and reduced lateral glueing on strap floors.
Fields of application	Can be used on all kinds of wood; special advantages on hard wood like oak or ash.
Method of application	Painting – soft acrylic brush Roller coating application – short haired roller
Ground pre-treatment	The ground has to be dry and free of impurities (e.g. oil, fat, wax) In case of small cracks and joints, wood final sanding with granulation 120, fill ground with a suitable filling mixture of 1 part by weight sanding dust und approx. 2 parts by weight ADLER Floor-Fill 42109. After about 1 hour drying again wood sanding with granulation 120.
Priming	Abundant application of ADLER Floor-Start 42110 . Do not dump ADLER Floor-Start 42110 on the floor. Drying about 2 hours. No sanding. Application for coloured floors on request!
Top coat	2 x ADLER Floor-Classic 42120 or 2 x ADLER Floor-Finish 42140. Slight intermediate sanding with gran. 240 or used sanding grid 120. Wipe sanding dust with wet cloth.
Thinning	The delivered drum size is ready to use and is not to be thinned.
Application and object temperatures	Not under + 10° C High air humidity and/or low temperatures delay drying. It is to be cared for good ventilation during drying time. Avoid direct sun insolation during application.
Drying time (Room temperature 20° C)	Can be overpainted after about 2 hours
Work equipment	Clean with water immediately after use. Remove remains of dried-on varnish with ADLER Abbeizer 95125.
Spreading rate (per application)	8 - 10 m ² /l

07-09 (replaces 07-07)

ADLER-Werk Lackfabrik, A-6130 Schwaz
Fon: 0043/5242/6922-450, Fax: 0043/5242/6922-399, Mail: info@adler-lacke.com

Our instructions are based on the current state of knowledge and serve to advise the buyer/user according to our best knowledge but without obligation and should be matched to the areas of application and processing conditions. It is the responsibility of the buyer to decide on suitability and use of the supplied product. Otherwise our general conditions of sale apply. All earlier information sheets cease to be valid with this edition. Subject to changes with regard to can size, shades of colour and available degrees of gloss.

Storage

Cool but frost-free

Drum sizes

1 l, 5 l

Storage life

1 year in original closed drums

Safety information

Please consider Safety Data Sheet!

Even when working with varnishes which are low in harmful substances, the usual protective measures are to be observed.