



RB2x70 FLOOR PRESTIGE

FIELD OF APPLICATION

Ceramic, stoneware, stone, concrete, cotto tiles and wood floorings.

INFORMATION

Floor Prestige is the high-tech, 1k matt coating for the renovation of floorings. Extremely resistant to foot traffic and abrasion, it is also suitable for surfaces with high traffic. Its water-based formula is odourless and with low VOC emissions, making this coating suitable for indoor spaces. Floor Prestige is a washable and high-covering product that strongly adheres to all kinds of surfaces carefully cleaned. In case of surfaces already coated, it is necessary to evaluate if a slight sanding of the old coating layer is required.

No primer application required.

Suitable for spaces, subject to HACCP standard.

The product is certified and complies with UNI 11021:2002 standard.

INSTRUCTIONS

Clean the surface from dirt, dust and grease by means of acetone, because these substances could avoid the adhesion of the coating. Do not apply over floorings, treated with oils, waxes or derivatives. Apply the product over the surface. Let it dry off (drying time between coats: min. 2 hours) before the application of the second coat. Two or three coats are recommended on surfaces subject to foot traffic. Ventilate the room after applying the product. On surfaces subject to wear, Floor Prestige can be protected with matt Floorings and furniture topcoat RP2260.

OVERCOATING

Floorings and furniture topcoat RP2260.

PACKAGING

0,75 L 2,5 L



Storage
> 5°C



Painting
> 10°C



Ready to use



Brush
Spray gun
Roller



Yield
14 m²/L



Mix it well
before use



Drying time
between the coats
2 h



Final drying time
24-72 h



Solid content
43 ± 5 %



Viscosity
DIN4 70 ± 10"



Specific weight
1,2 ± 0,1 g/cm³



pH
8,5 ± 1,0



Gloss level
20



RB2070
DOVE GREY



RB2170
PAPYRUS



RB2270
CONCRETE



RB2370
LEAD



RB2470
CHARCOAL GREY