

## FIELD OF APPLICATION

Wood, metal, glass, plastic, wall, fabric, steel and galvanised steel sheet. For indoor and outdoor use.

#### INFORMATION

Vintage Prestige is a ultra-matt enamel. It is a high-covering product, which strongly adheres to all kinds of surfaces. Its formula is odourless and with low VOC emissions. Vintage Prestige is a washable product. No sanding, no stripping, no primer application required. The application of two coats is recommended.

### **INSTRUCTIONS**

Clean the surface from dirt, dust and grease by means of acetone, because these substances could avoid the adhesion of the coating. If old coatings peeled off, sand with 150-180 grit sandpaper. Spread the product on the surface. After 2 hours it is possible to apply a second coat. To decorate rusty metal surfaces, remove the rust with sandpaper or metallic brush. Apply an antirust, then apply Vintage Prestige products.

#### **OVERCOATING**

Natural Effect Topcoat RO3000.

# **PACKAGING**

0,5 L

5 L \*

\*only RB1490, RB2090, RB2190

















**RB1090** DARK CHERRY













**RB1190** MILKSHAKE



**RB1490** COCONUT



**RB1790 JUNIPER** 



**RB2090** MILK













**RB1590** MINTGREEN



**RB1890** TRUFFLE



**RB2190** LICORICE





Storage > 5°C



Painting > 10°C



Ready to use



Brush Sponge Roller



Yield 8-10 m<sup>2</sup>/L



Mix it well before use



Drying time between the coats 2 h



Final drying time 6-8 h



Solid content  $60 \pm 10 \%$ 



Viscosity  $14000 \pm 1000 \text{ cps}$ 



Specific weight  $1.2 \pm 0.2 \text{ g/cm}^3$ 



Gloss level



Watch our tutorials

