

PROJEKT 2



Fully-matt paint for ceilings

- Reflection-free
- High whiteness
- When applying doesn't splash
- High coverability - class 2 (10m²/l) EN13300

Product description

A ceiling paint developed together with professional painters, creates a smooth, perfectly matt surface and prevents light glare. The paint is easy to apply, does not splatter when painting, and creates a smooth, fully-matt finish. A specially extended surface drying time facilitates obtaining an even smooth surface. On well-prepared surfaces, one coat of paint is usually sufficient thanks to its double coverage. Designed for painting ceilings as well as walls in dry living and public areas with no special requirements for wear resistance and washing.

Suitable for new and pre-painted concrete, plaster, plasterboard, fibreboard, primed metal, fibreglass and paintable wallpaper surfaces in interior projects.



Swedish paint
Since 1955

| | |
|--------------------------------|--|
| Area of application | Indoors |
| Binder | VAE |
| Volume Solids | 32% |
| Weight Solids | 51% |
| Density | 1,40 kg/l |
| Gloss | 1, fully matt |
| Spreading rate | 10 m ² /l |
| Hiding power | Class 2 |
| Material consumption | depends on the application method, conditions, shape and roughness of the surface to be treated 7–10 m ² /l |
| Thinner/Cleaning | Water |
| Temperature at painting | Minimum +5°C |
| Tools for painting | Brush, roller or spray |
| Dust dry | 1 h |
| Re-paintable | 2 h |
| Completely dry | 24 h |
| Shelf life | 2 years if unopened, frost free storage |
| Colour | White and tintable in light shades |
| Flammability | Not flammable |
| VOC category | (Cat. A/a): <30 g/l |
| Transportation | Protect from frost |
| Wet-scrub resistance | 3. class EN 13300; <75µm ISO 11998 |

How to use

Surface preparation and application conditions

Mechanically remove peeling paint from previously painted surfaces. Surfaces painted with chalk or lime paint, as well as crumbling and highly absorbent surfaces, must be mechanically cleaned and primed with MICRO Tiefgrund. Disinfect mouldy surfaces using a special agent according to the instructions for use. Areas damaged by moisture or yellowed from nicotine should be primed with a special priming paint. Prime metal parts or rusting screws with an anti-corrosion primer. Wash new galvanized surfaces with a suitable detergent and degreaser. Glossy and very smooth surfaces should be sanded matte with sandpaper. If necessary, putty and level the surface with a high-quality putty. The surface to be painted must be clean, dry and uniform. Porous plaster and concrete surfaces, unevenly absorbent surfaces, as well as partially plastered plasterboard surfaces are recommended to be primed with PROJEKT Primer prior to painting.

If it is necessary to repaint very bright or very dark painted surfaces with a contrasting colour tone, it is recommended to first prime the entire surface with lightly tinted PROJEKT Primer.

During painting, air and surface temperature cannot be lower than +5°C and air humidity cannot exceed 80%.

Application

Mix the paint thoroughly before use. The paint is ready for use, but if necessary, it can be slightly diluted with water. To avoid the difference in shades, mix all the required amount of paint in one container, or continuously refill the paint container in use with paint from the next can. Paint with a brush or roll 1-2 times. When painting with a sprayer, dilute the paint with a bit of water. Repaint after 2-3 hours. Allow the surface to dry well before applying the next layer.

To avoid paint joint lines, follow the "wet-on-wet" method when painting, applying the coating in one go without stops. Use enough paint on the roller so that the colour is even. If you are right-handed, paint the wall from left to right across the entire surface from bottom to top. If you are left-handed, from right to left respectively. When painting the ceiling, paint in a cross pattern, but paint the last layer in the direction of the light.

Surface treatment

Surface cleaning can be done no earlier than 1 month after

painting. Use a sponge or cloth dampened in water or a neutral detergent solution to clean the surface. After cleaning, rinse the surface with clean water. Never use alcohol to clean painted or varnished surfaces unless specifically stated in the paint product description.

Transportation and storage

Store in dry and cool place in unopened original packaging. Protect from frost. Shelf life 2 years from the date of manufacture.

Environmental and labor protection, waste collection

Use personal protective equipment. Ensure good ventilation when sanding treated surfaces. Wipe instruments thoroughly before washing with water. Close the jar carefully after use and keep it out of the reach of children. Liquid residues must not be drained into the sewer but must be taken to a local collection point.

Recycle empty, dry cans or dispose them of in accordance with local regulations.

Protect the environment, like we do!

Keep out of children. Contains a biocidal product: C(M)IT/MIT (3:1). May produce an allergic reaction. Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. This product contains a maximum of 30 g VOC/L. The limit value is 30 g VOC/L (cat. A/a)

The above information is based on our existing knowledge, laboratory tests, experience and information that the manufacturer has been able to provide at the time of preparing the product specification. The manufacturer's management system is certified and complies with the international standards ISO 9001 and ISO 14001. The manufacturer and the distributor have no control over the conditions of use or other factors that may affect the use and application of the product. The buyer/user is responsible for the suitability and use of the product. Please note that all of the above concerning the use of the product is dependent on the correct preparation of the surface and the surrounding environment.