

## KOLOREX Wood Stain



### Waterborne wood stain for exterior wooden surfaces

- Highlights the natural look of wood
- Protect wood against water penetration
- Provides UV protection
- Contains antiseptic additives

### Product description

Semi-matt transparent waterborn wood stain for previously untreated or oiled outdoor wood surfaces. KOLOREX Wood Stain is based upon a unique alkyd oil and acrylic combination which provides high protection against water penetration. The product is highly water-resistant and retards the negative impacts of moisture and UV light on timber. Mostly used tinted in natural wood tones. The richer and darker the chosen glaze shade, the longer lasting the wood protection. Suitable for finishing logs, sawn and planed wood surfaces, as well as for log houses. Gives wood a transparent, natural look and accentuates the natural texture of the wood. Contains anti-mold additives.

Not recommended for horizontal surfaces such as terraces.



Swedish paint  
Since 1955

<b>Area of application</b>	Outdoors
<b>Binder</b>	Alkyd/acrylate
<b>Volume Solids</b>	20%
<b>Density</b>	1,02 kg/l
<b>Gloss</b>	Semi matt
<b>Thinner/Cleaning</b>	Water
<b>Material consumption</b>	5-8 m <sup>2</sup> /l sawn wood, 7-12 m <sup>2</sup> /l planed wood
<b>Temperature at painting</b>	Minimum +5°C
<b>Tools for painting</b>	Brush
<b>Dust dry</b>	6 h
<b>Re-paintable</b>	12 h
<b>Shelf life</b>	2 years if unopened, frost free storage
<b>Colour</b>	Colorless, tintable in shades intended for outdoor use
<b>Flammability</b>	Not flammable
<b>VOC category</b>	(Cat. A/e): 130 g/l (2010)

## How to use

### Surface preparation and application conditions

The surface must be clean and dry, with the moisture content in the wood less than 18%. Air, surface and material temperature should be above +5°C and the relative humidity during application and drying should be below 80%. Brush or scrape off loose old paint and /or porous and degraded wood. If necessary, wash the surface with a suitable cleaner or water. In case of black mould or algae stains, treat the surface with an anti-mould disinfectant, rinse thoroughly with water, and allow it to dry completely.

Prime untreated wood with KOLOREX Priming Oil according to the product's instructions. While applying primer, pay special attention to the ends of the boards, the places of sawing, location points of screws and nails.

### Application

Mix thoroughly before use. Apply 1-2 coats. Cover the entire length of the board to achieve a uniform application. When applied in several layers, the covering will be darker and more opaque. Do not paint in cold or wet conditions for prolonged periods, also do not work in extremely hot weather and in direct sunlight.

### Transportation and storage

Store in dry and cool place in unopened original packaging. Protect from frost. Shelf life 2 years from the date of manufacture

### Environmental and labor protection, waste collection.

Use personal protective equipment. Ensure good ventilation when sanding treated surfaces. Wipe off the tools thoroughly before cleaning with water. Close the jar carefully after use and keep out of the reach of children. Liquid residues must not be drained into the sewer but must be taken to a local collection point.

Recycle empty, dry cans or dispose them of in accordance with local regulations.

### Protect the environment, like we do.

---

Harmful to aquatic life with long lasting effects. Keep out of reach of children. Avoid release to the environment. Dispose of contents/container in accordance with local regulations. Contains biocide: BIT, C(M)IT/MIT (3:1). Contains a biocidal product for the

preservation of dry-film: IPBC, OIT, diuron (ISO). May produce an allergic reaction.

This product contains a maximum of 130 g VOC/L. The limit value is 130 g VOC/L (cat. A/f).

The above information is based on our existing knowledge, laboratory tests, experience and information that the manufacturer has been able to provide at the time of preparing the product specification. The manufacturer's management system is certified and complies with the international standards ISO 9001 and ISO 14001. The manufacturer and the distributor have no control over the conditions of use or other factors that may affect the use and application of the product. The buyer/user is responsible for the suitability and use of the product. Please note that all of the above concerning the use of the product is dependent on the correct preparation of the surface and the surrounding environment.