



Floor Prestige | RB2x70

Field of application. Ceramic, tiles, stoneware, stone, concrete, terracotta, wall, wood, glass, plastic, PVC, metal surfaces.

Information. Floor Prestige is the high-tech, 1k matt coating for the renovation of floorings and all kinds of surfaces. Extremely resistant to foot traffic and abrasion, it is also suitable for surfaces with high foot traffic. Its formula is odourless and with low VOC emissions. Floor Prestige is a washable and high-covering product that strongly adheres to all kinds of surfaces carefully cleaned. In case of surfaces already coated, it is necessary to evaluate if a slight sanding of the old coating layer is required. For coating interior and exterior floorings, add 4% of Adhesion Promoter RY0406 to Floor Prestige. RY0406 strengthens the bond with the surface to be coated and increases the resistance of the coating.

No primer application required. Suitable for spaces, subject to HACCP standard. The product is certified and complies with UNI 11021:2002 standard.

Instructions. Before the application. Remove dust and grease by means of Clean & Grip VY0500. Do not use other degreasers or thinners available on the market: they could leave residuals on the surface and compromise the adhesion of Floor Prestige. *How to prepare a surface treated with wax.* Before applying Floor Prestige, remove the wax with a dewaxer; then rinse and degrease by means of Clean & Grip VY0500. *How to prepare a very smooth surface.* On particularly smooth surfaces, such as marble, slightly sand with 220 grit sandpaper for metal. It is fundamental removing completely the dust. Slightly sanding, specifically suitable for the treatment of smooth substrates, is useful for every surface since they promote the coating adhesion. *How to treat grout lines.* Grout lines between tiles are porous. Therefore, they accumulate dirt compromising the coating adhesion and the aesthetic result. Cleaning grout lines is very important and it could be done mechanically by means of steel brush or other tools. *How to treat surfaces under extreme stress.* Add 4% of Adhesion Promoter RY0406 to Floor Prestige range in case of surfaces under severe chemical and/or mechanical stress (bath tubs, gym floorings, laboratories floorings, clinics, hair salons, pet grooming services, etc.). Adhesion Promoter strengthens the bond with the surface to be coated and improves coating resistances. **Application.** Spread the product over the surface. Before the application of the second coat, let it dry off at least 2-4 hours according to the environmental conditions. 2 or 3 coats are suggested for surfaces with high traffic. On surfaces highly subjected to wear, Floor Prestige can be protected with Floorings and Furniture Topcoat RP2260. **Drying.** Carefully ventilate the room to promote the correct drying of Floor Prestige. In order to get a state-of-the-art drying, avoid too much abundant application; excessive weight of product could impede a complete drying, leaving the coating wet and less performing.

Overcoating. Floorings and Furniture Topcoat RP2260.

Packaging. 0,75 L 2,5L



Storage
> 5°C



Painting
> 10°C



Ready to use



Brush
Spray gun
Roller



Yield
14 m²/L



Mix it well
before use



Tack-free
2 h



Drying time
between the coats
4-6 h



Final drying time
24-72 h



Solid content
43 ± 5 %



Viscosity
DIN4 70 ± 10"



Specific weight
1,2 ± 0,1 g/cm³



pH
8,5 ± 1,0



Gloss level
20



RB2070
dove grey



RB2170
papyrus



RB2270
concrete



RB2370
lead



RB2470
charcoal grey



RB2570
titanium



Watch our tutorials

HACCP





H₂O

Floor Prestige neutral and white base | RBNT70 RBBC70

Field of application. Ceramic, tiles, stoneware, stone, concrete, terracotta, wall, wood, glass, plastic, PVC, metal surfaces.

Information. Floor Prestige neutral and white base must be pigmented to provide resistance to foot traffic and abrasion as the ready-to-colors. The pigmented base is also suitable for surfaces with high foot traffic. For coloring RBNT70 and RBBC70 do not exceed the addition of 10% EY---M690 pastes. Its formula is odourless and with low VOC emissions. Floor Prestige pigmented base is a washable and high-covering product that strongly adheres to all kinds of surfaces carefully cleaned. In case of surfaces already coated, it is necessary to evaluate if a slight sanding of the old coating layer is required. For coating interior and exterior floorings, add 4% of Adhesion Promoter RY0406 to Floor Prestige pigmented base. RY0406 strengthens the bond with the surface to be coated and increases the resistance of the coating. **No primer application required. Suitable for spaces, subject to HACCP standard. The product is certified and complies with UNI 11021:2002 standard.**

Instructions. Before the application. Remove dust and grease by means of Clean & Grip VY0500. Do not use other de-greasers or thinners available on the market: they could leave residuals on the surface and compromise the adhesion of Floor Prestige pigmented base. *How to prepare a surface treated with wax.* Before applying Floor Prestige pigmented base, remove the wax with a dewaxer; then rinse and degrease by means of Clean & Grip VY0500. *How to prepare a very smooth surface.* On particularly smooth surfaces, such as marble, slightly sand with 220 grit sandpaper for metal. It is fundamental removing completely the dust. Slightly sanding, specifically suitable for the treatment of smooth substrates, is useful for every surface since they promote the coating adhesion. *How to treat grout lines.* Grout lines between tiles are porous. Therefore, they accumulate dirt compromising the coating adhesion and the aesthetic result. Cleaning grout lines is very important and it could be done mechanically by means of steel brush or other tools. *How to treat surfaces under extreme stress.* Add 4% of Adhesion Promoter RY0406 to Floor Prestige pigmented base in case of surfaces under severe chemical and/or mechanical stress (bath tubs, gym floorings, laboratories floorings, clinics, hair salons, pet grooming services, etc.). Adhesion Promoter strengthens the bond with the surface to be coated and improves coating resistances. **Application.** Spread the product over the surface. Before the application of the second coat, let it dry off at least 2-4 hours according to the environmental conditions. 2 or 3 coats are suggested for surfaces with high traffic. On surfaces highly subjected to wear, Floor Prestige pigmented base can be protected with Floorings and Furniture Topcoat RP2260. **Drying.** Carefully ventilate the room to promote the correct drying of Floor Prestige pigmented base. In order to get a state-of-the-art drying, avoid too much abundant application; excessive weight of product could impede a complete drying, leaving the coating wet and less performing.

Overcoating. Floorings and Furniture Topcoat RP2260.

Packaging. RBNT70 0,92 kg 4,6 kg RBBC70 1 kg 5 kg



RBNT70
white base
20 gloss



RBBC70
neutral base
20 gloss



Storage
> 5°C



Painting
> 10°C



To be pigmented



Brush
Spray gun
Roller



Yield
10-14 m²/L



Mix it well
before use



Tack-free
2 h



Drying time
between the coats
4-6 h



Final drying time
24-72 h



Foot traffic
after 72 h



Solid content
43 ± 5 %



Viscosity
DIN4 70 ± 10"



Specific weight
RBNT70 1,08 ± 0,03 g/cm³
RBBC70 1,18 ± 0,03 g/cm³



Gloss
20 ± 10



Watch our tutorials

HACCP

