

## KOLOREX Primer Aqua



### Alkyd water-based primer for for outdoor wood surfaces

- Creates a good adhesive surface
- Good covering capacity
- Penetrates deeply into wood surfaces

### Product description:

A water-based oil primer designed for preparing exterior wooden surfaces prior to painting with alkyd and acrylic paints. This primer is suitable for untreated sawn and planed wooden surfaces, as well as surfaces previously coated with alkyd and acrylic paints. It provides excellent coverage and deeply penetrates the wood surface, resulting in a matte finish that is easy to repaint.

KOLOREX Primer Aqua is an excellent choice for projects with tight deadlines, where the use of products with faster drying times and lower VOC content is required.

Kolorex Primer Aqua is produced in Sweden.



Swedish paint  
Since 1955

<b>Area of application</b>	Outdoors
<b>Binder</b>	Alkyd / oil
<b>Volume Solids</b>	31%
<b>Weight Solids</b>	45%
<b>Density</b>	1,26 kg/l
<b>Gloss</b>	Fully matt
<b>Washability</b>	Class 1 (EN 13300)
<b>Thinner/Cleaning</b>	Water
<b>Material consumption</b>	6-10 m <sup>2</sup> /L
<b>Temperature at painting</b>	Minimum +5°C
<b>Tools for painting</b>	Brush, roller and spray
<b>Dust dry</b>	4 h
<b>Re-paintable</b>	6-8 h
<b>Completely dry</b>	48 h
<b>Shelf life</b>	2 years if unopened, frost free storage
<b>Colour</b>	White
<b>Flammability</b>	Not flammable
<b>VOC category</b>	(Cat. A/d): 130 g/l (2010)

# KRASO

## How to use

### Surface preparation and application conditions

The surface must be clean and dry, with the moisture content in the wood less than 18%. Air, surface and material temperature should be above +5°C and the relative humidity during application and drying should be below 80%. Brush or scrape off loose old paint and /or porous and degraded wood. If necessary, wash the surface with a suitable cleaner or water. In case of black mould or algae stains, treat the surface with an anti-mould disinfectant, rinse thoroughly with water, and allow it to dry completely.

Prime untreated wood with KOLOREX Priming Oil according to the product's instructions. While applying primer, pay special attention to the ends of the boards, the places of sawing, location points of screws and nails.

### Application

Stir thoroughly before use. Apply one or two coats. For new, previous not treated wood, we recommend at least two coats. Avoid application on hot or sunlit surfaces.

### Transportation and storage

Store in dry and cool place in unopened original packaging. Protect from frost. Shelf life 2 years from the date of manufacture

### Environmental and labor protection, waste collection

Use personal protective equipment. Ensure good ventilation when sanding treated surfaces. Wipe off the tools thoroughly before cleaning with water. Close the jar carefully after use and keep out of the reach of children. Liquid residues must not be drained into the sewer, but must be taken to a local collection point.

### Protect the environment, like we do!

---

#### Warning

May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

Keep out of reach of children. Avoid release to the environment. IF ON SKIN: Wash with plenty of soap and water. Dispose of

contents/container in accordance with local regulations.

Contains: 3-iodo-2-propynyl butylcarbamate, 2-octyl-2H-isothiazol-3-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one un 2-methyl-2H-isothiazol-3-one (3:1).

Contains biocidal product: C(M)IT/MIT (3:1).

Contains biocidal product for the preservation of dry-film: OIT, IPBC.

This product contains a maximum of 130 g VOC/L. The limit value is 130 g VOC/L (cat. A/d).

The above information is based on our existing knowledge, laboratory tests, experience and information that the manufacturer has been able to provide at the time of preparing the product specification. The manufacturer's management system is certified and complies with the international standards ISO 9001 and ISO 14001. The manufacturer and the distributor have no control over the conditions of use or other factors that may affect the use and application of the product. The buyer/user is responsible for the suitability and use of the product. Please note that all of the above concerning the use of the product is dependent on the correct preparation of the surface and the surrounding environment.