

KOLOREX Terrace Oil



Oil for exterior wood surfaces

- Creates a water and dirt repellent surface
- Prevent blue stain and mould growth
- Decreases cracking of wood surface
- High UV resistance

Solvent-based, silicone-alkyd oil is suitable for exterior wood surfaces. It contains tung wood oil, which ensures deep penetration into the wood and protects it from moisture. It decreases cracking, blue stain, and mold growth on wood surfaces. It is suitable for impregnated wood, wood previously treated with oil, and untreated wood. It can be used for hardwood or exotic wood species. The oil gives wood a transparent, natural look and accentuates its natural structure. Oil protects the wood from moisture and UV sunlight, it quickly absorbs and does not create a film on the surface.

Suitable for various wooden outdoor surfaces, such as terraces, garden furniture, stairs, and piers.



Swedish paint
Since 1955

Area of application	Outdoors
Binder	Silicon alkyd, Alkyd and Tung tree oil
Volume Solids	30%
Weight Solids	35%
Density	0,86 kg/l
Thinner/Cleaning	White spirit/Naphtha
Material consumption	4–7 m ² /L. sawn wood, 7–12 m ² /L. planed wood
Temperature at painting	Minimum +5°C
Tools for painting	Brush, dipping or cloth
Dust dry	8 h
Re-paintable	16 h
Shelf life	2 years if unopened, frost free storage
Colour	Clear
Flammability	3
VOC category	(Cat. A/f): 700 g/l (2010)
Gloss	Dependent on surface

How to use

Surface preparation and application conditions

The surface must be clean and dry, with the moisture content in the wood 12-16%. Air, surface and material temperature should be above +5°C and the relative humidity during application and drying should be below 80%. In case of black mould or algae stains, treat the surface with an anti-mould disinfectant, rinse thoroughly with water, and allow it to dry completely.

Application

Stir the oil thoroughly in the can before use. Apply generously by brushing or dipping. The oil must be completely absorbed into the wood without leaving a film on the surface. Apply especially thoroughly to the ends of boards, joints, nail and screw placing points. Apply several times until the wood no longer absorbs the oil. Clean the areas where the oil has not soaked in and the twig points with a cloth soaked in white spirit. Do not apply in direct sunlight or on surfaces that are excessively heated. The solvent evaporates too quickly in the heat and reduces the penetration of the oil deep into the wood.

N.B.! As rags soaked in oil can self-ignite, store them in water or dry them in the open air until disposal, or burn them immediately!

Maintenance

Clean with a soft brush and water, to which a little mild detergent can be added.

Storage

Store in dry and cool place in unopened original packaging. Shelf life is 2 years from the date of manufacture.

Environmental and labor protection, waste collection

Use personal protective equipment. Ensure good ventilation when sanding treated surfaces. Wipe off the tools thoroughly before cleaning with white spirit. Close the jar carefully after use and keep out of the reach of children. Liquid residues must not be drained into the sewer, but must be taken to a local collection point.

Protect the environment, like we do.

Keep out of reach of children. Keep away from heat, hot surfaces,

The above information is based on our existing knowledge, laboratory tests, experience and information that the manufacturer has been able to provide at the time of preparing the product specification. The manufacturer's management system is certified and complies with the international standards ISO 9001 and ISO 14001. The manufacturer and the distributor have no control over the conditions of use or other factors that may affect the use and application of the product. The buyer/user is responsible for the suitability and use of the product. Please note that all of the above concerning the use of the product is dependent on the correct preparation of the surface and the surrounding environment.

sparks, open flames and other ignition sources. No smoking. Dispose of contents/container in accordance with local regulations. Contains a biocidal product for the preservation of dry-film: IPBC. May produce an allergic reaction. Contains Tung oil. Risk of spontaneous combustion. Spills and used cloths are to be collected and deposited in a fireproof waste container, hung to dry outdoors or burned under supervision.

This product contains a maximum of 700 g VOC/L. The limit value is 700 g VOC/L (cat. A/f)