

## PROJEKT PRIMER Aqua



### Damp-proofing and adhesive for wet areas in interior work

- Forms a damp-proof surface
- High coverage
- Contains anti-mould additives

### Product description

Projekt Primer Aqua is a high-quality moisture-insulating primer and adhesive for walls and ceilings in damp indoor environments. Suitable for bonding fibreglass and other materials, as well as for priming surfaces in bathrooms, shower rooms, kitchens and other wet areas. The primer forms a dense, water-resistant and moisture-insulating film. It contains fungicides that protect the paint film and prevents the formation of mould on the painted surface. Suitable for priming concrete, plaster, plasterboard, fibreboard, fibreglass and paintable wallpaper in interior applications.

The primer has very good coverage and filling power, so it gives the surface paint a uniform gloss. It helps to create a smooth surface for the application of different topcoats and also helps to reduce the amount of topcoat to be applied.



Swedish paint  
Since 1955

<b>Area of application</b>	Indoors
<b>Binder</b>	Styrene Acrylic
<b>Volume Solids</b>	44%
<b>Weight Solids</b>	46%
<b>Density</b>	1.04 kg/l
<b>Thinner/Cleaning</b>	Water
<b>Material consumption</b>	ca 5-10 m <sup>2</sup> /l depends on the application method, conditions, shape and roughness of the surface to be treated
<b>Temperature at painting</b>	+5°- +30°C
<b>Tools for painting</b>	Brush/roller/spray
<b>Dust dry</b>	Ca 1 h (20°C, 60%RF)
<b>Re-paintable</b>	3 h
<b>Completely dry</b>	24 h
<b>Shelf life</b>	2 years
<b>Colour</b>	light blue
<b>Transportation</b>	Protect from frost

## How to use

### Surface preparation and application conditions

Mechanically remove peeling paint from previously painted surfaces. Surfaces painted with chalk or lime paint, as well as crumbling and highly absorbent surfaces, must be mechanically cleaned and primed with MICRO Tiefgrund. Disinfect mouldy surfaces using a special agent according to the instructions for use. Areas damaged by moisture or yellowed from nicotine should be primed with a special priming paint. Prime metal parts or rusting screws with an anti-corrosion primer. Wash new galvanized surfaces with a suitable detergent and degreaser. Glossy and very smooth surfaces should be sanded matte with sandpaper. If necessary, putty and level the surface with a high-quality putty. The surface to be painted must be clean, dry and uniform.

During painting, air and surface temperature cannot be lower than +5°C and air humidity cannot exceed 80%.

### Application

Mix the paint thoroughly before use. The paint is ready for use, but if necessary, it can be slightly diluted with water. Paint with a brush or roll. When painting with a sprayer, dilute the paint with a bit of water. Repaint after 3 hours. Allow the surface to dry well before applying the next layer.

To avoid paint joint lines, follow the "wet-on-wet" method when painting, applying the coating in one go without stops. Use enough paint on the roller so that the colour is even. If you are right-handed, paint the wall from left to right across the entire surface from bottom to top. If you are left-handed, from right to left respectively. When painting the ceiling, paint in a cross pattern, but paint the last layer in the direction of the light.

When wallpapering, use the wet-on-wet method.

### Transportation and storage

Store in dry and cool place in unopened original packaging. Protect from frost. Shelf life 2 years from the date of manufacture.

### Environmental and labor protection, waste collection

Use personal protective equipment. Ensure good ventilation when sanding treated surfaces. Wipe instruments thoroughly before washing with water. Close the jar carefully after use and keep it out of the reach of children. Liquid residues must not be drained into the sewer but must be taken to a local collection point.

The above information is based on our existing knowledge, laboratory tests, experience and information that the manufacturer has been able to provide at the time of preparing the product specification. The manufacturer's management system is certified and complies with the international standards ISO 9001 and ISO 14001. The manufacturer and the distributor have no control over the conditions of use or other factors that may affect the use and application of the product. The buyer/user is responsible for the suitability and use of the product. Please note that all of the above concerning the use of the product is dependent on the correct preparation of the surface and the surrounding environment.

Recycle empty, dry cans or dispose them of in accordance with local regulations.

### Protect the environment, like we do!

---

Keep out of reach of children. Contains biocidal products: BIT, C(M)IT/MIT (3:1). May produce an allergic reaction.

This product contains a maximum of 30 g VOC/L. The limit value is 30 g VOC/L (cat. A/a).