

PROJEKT PRO 2

Fully-matt paint for ceilings

- Reflection-free
- High whiteness
- Creates a uniform, smooth surface.

Product description

Developed together with professional painters, this paint for ceilings creates a distinctly smooth, completely matte surface that eliminates light reflections. The paint is easy to apply, does not splash when rolling, and allows for touch-ups on previously painted areas without the need to repaint the entire surface. It is designed for painting ceilings as well as walls in dry residential and public spaces, where there are no specific requirements for wear resistance or washability.

Suitable for new and previously painted surfaces such as concrete, plaster, drywall, fiberboard, fiberglass, and paintable wallpaper indoors.

PROJEKT 7 Aqua has the certification of M1. Product can be used in BREEAM certified buildings.



Swedish paint
Since 1955

Area of application	Indoors
Binder	VAE
Volume Solids	37%
Weight Solids	58%
Density	1,44 kg/l
Gloss	2, fully matt
Spreading rate	8 m ² /l
Hiding power	Class 2
Material consumption	7-10 m ² /l
Washability	Class 2
Thinner/Cleaning	Water
Temperature at painting	Minimum +5°C
Tools for painting	Brush, roller or spray
Dust dry	1 h
Re-paintable	2 h
Completely dry	24 h
Shelf life	2 years if unopened, frost free storage
Colour	White
Flammability	Not flammable
VOC category	(Cat. A/a): <30 g/l, VOC content of the product <3 g/l
Transportation	Protect from frost
Producer	Hagmans Nordic AB, Sweden

How to use

Surface preparation and application conditions

Mechanically remove peeling paint from previously painted surfaces. Surfaces painted with chalk or lime paint, as well as those that are crumbling and highly absorbent, require mechanical cleaning and priming with MICRO Tiefgrund. For disinfecting moldy surfaces, use a specialized agent following the provided instructions. If there are areas damaged by moisture or discolored by nicotine, apply a special primer. Metal parts and rusting screws should be treated with an anti-corrosion primer. Wash new galvanized surfaces with an appropriate detergent and degreaser. Glossy and ultra-smooth surfaces should be sanded to achieve a matte finish using sandpaper. If needed, apply a high-quality putty to level the surface. Ensure that the surface to be painted is clean, dry, and uniform. Prior to painting, it's advisable to prime porous plaster and concrete surfaces, surfaces with uneven absorption, as well as partially plastered plasterboard surfaces with PROJEKT Primer.

If repainting is required for surfaces with very bright or very dark colors and a contrasting color tone, it is advisable to start by priming the entire surface with lightly tinted PROJEKT Primer. For painting bright colors such as yellows, reds, and other vivid shades, it's recommended to prime the whole surface with PROJEKT Primer tinted in a shade similar to the intended color.

During painting, air and surface temperature cannot be lower than +5°C and air humidity cannot exceed 80%.

Application

Mix the paint thoroughly before use. The paint is ready for use, but if necessary, it can be slightly diluted with water. To avoid the difference in shades, mix all the required amount of paint in one container, or continuously refill the paint container in use with paint from the next can. Paint with a brush or roll 1-2 times. When painting with a sprayer, dilute the paint with a bit of water. Repaint after 1-2 hours. Allow the surface to dry well before applying the next layer.

To avoid paint joint lines, follow the "wet-on-wet" method when painting, applying the coating in one go without stops. Use enough paint on the roller so that the colour is even. If you are right-handed, paint the wall from left to right across the entire surface from bottom to top. If you are left-handed, from right to left respectively. When painting the ceiling, follow a cross pattern, and

make sure the final coat is applied in the direction of the light.

Surface treatment

Surface cleaning can be done no earlier than 1 month after painting. Use a sponge or cloth dampened in water or a neutral detergent solution to clean the surface. After cleaning, rinse the surface with clean water. Never use alcohol to clean painted or varnished surfaces unless specifically stated in the paint product description.

Transportation and storage

Store in dry and cool place in unopened original packaging. Protect from frost. Shelf life 2 years from the date of manufacture.

Environmental and labor protection, waste collection

Protect skin and eyes from splashes. Avoid inhaling spray mist and sanding dust. Paint and cleaning liquids must not be disposed of in drains but should be collected and handled as environmental waste. Close the jar carefully after use and keep it out of the reach of children.

Empty Containers. Sort empty and dry containers as plastic. Metal handles should be removed and sorted as metal. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Liquid residues must not be drained into the sewer but must be taken to a local collection point. Minimize paint wastage by estimating how much paint you will need. Recover unused paint for re-use. Reuse of paint can effectively minimize the products life cycle environmental impact.

Protect the environment, like we do!

The above information is based on our existing knowledge, laboratory tests, experience and information that the manufacturer has been able to provide at the time of preparing the product specification. The manufacturer's management system is certified and complies with the international standards ISO 9001 and ISO 14001. The manufacturer and the distributor have no control over the conditions of use or other factors that may affect the use and application of the product. The buyer/user is responsible for the suitability and use of the product. Please note that all of the above concerning the use of the product is dependent on the correct preparation of the surface and the surrounding environment.