



RS3010 UNIFORM PLUS

FIELD OF APPLICATION

Wood, metal, plastic, PVC, glass, ceramic, steel, galvanised steel sheet, plaster, plasterboard. For indoor and outdoor use.

INFORMATION

Uniform Plus is a white water-based multi-surface primer, made of acrylic resins, suitable for the application on materials, that are difficult to be coated, such as doors, windows, wood claddings and other materials. In case of application on wood, Uniform Plus is an anti-tannin product, therefore it stops the migration of wood extractives, i.e. tannins and oily substances. Uniform Plus effectively covers coffee, marker, pastel, rust and old coatings stains. The thixotropic features make the product particularly suitable for vertical application.

INSTRUCTIONS

Raw wood. Sand with 150-180 grit sandpaper, clean the surface from dust and grease and apply 2-3 coats of product.

Coated wood. Sand with 180-240 grit sandpaper. If some coating films peeled off, make sure to remove them completely. Clean the surface from dust and grease, then apply Uniform Plus in 2-3 coats.

Other surfaces. Before the application, clean the surface from dust and grease. To improve the application, it is possible to sand slightly the support with 180-240 grit sandpaper and apply 2 or 3 coats of product. To decorate rusty metal surfaces, remove the rust with sandpaper or metallic brush. Apply an antirust product, then apply Uniform Plus.

OVERCOATING

Decopig Solution RE20xx, Prestige range RBxxx0, Floorings and Furniture Topcoat RPxx60, Natural Effect Topcoat RO3000.

PACKAGING

0,5 L

2,5 L



Storage
> 5°C



Painting
> 10°C



Ready to use
Brush or roller
Dilution max. 10%
Spray gun



Brush
Spray gun
Roller



Yield
8-12 m²/L



Mix it well
before use



Drying time
between the coats
4-24 h



Final drying time
24 h



Solid content
58 ± 3 %



Viscosity
5000 ± 300 cps



Specific weight
1,3 ± 0,1 g/cm³



pH
8,5 ± 1,0

