

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: Kraso Kolorex Wood Paint Matt

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: Paint

1.3. Details of the supplier of the safety data sheet

Supplier

Company: Kraso SIA
Address: Vienības gatve 93
Zip code: LV-1058
City: Rīga
Country: LATVIA
Email: info@kraso.com
Phone: +371 67887192

1.4. Emergency Telephone Number

See phone number in section 1.3

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

CLP-classification: Aquatic Chronic 3;H412

Most serious harmful effects: Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard Statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P273 Avoid release to the environment.
P501 Dispose of contents/container in accordance with local regulations.

Supplemental information

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Contains biocidal products: BIT, Bronopol and C(M)IT/MIT (3:1) Contains biocidal product for the preservation of dry-film: Terbutryn and IPBC. May produce an allergic reaction.

VOC: This product contains a maximum of 50 g VOC/L. The limit value is 130 g VOC/L (cat. A/d)

2.3. Other hazards

The substance/mixture contains no components considered to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB) in concentrations of 0.1% or higher.

The substance/mixture contains no components that are considered to have endocrine-disrupting properties according to REACH art. 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substance	CAS No./ EC No./ REACH Reg. No.	Concentration	Notes	CLP-classification
Bronopol	52-51-7 200-143-0	< 0.05 %		Acute Tox. 3;H301 Acute Tox. 4;H312 Skin Irrit. 2;H315 Eye Dam. 1;H318 Acute Tox. 3;H331 STOT SE 3;H335 Aquatic Acute 1;H400 Aquatic Chronic 2;H411 M (acute): 10
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 01-2120761540-60	< 0.036 %		Acute Tox. 4;H302 Skin Irrit. 2;H315 Skin Sens. 1A;H317 Eye Dam. 1;H318 Acute Tox. 2;H330 Aquatic Acute 1;H400 Aquatic Chronic 1;H410 C ≥ 0.036%: Skin Sens. 1A;H317 ATE (dust/mist) (Acute toxicity - inhalation): 0.21 mg/l ATE (Acute toxicity - oral): 450 mg/kg bw M (acute): 1 M (chronic): 1
3-iodo-2-propynyl butylcarbamate	55406-53-6 259-627-5	< 0.015 %		Acute Tox. 4;H302 Skin Sens. 1;H317 Eye Dam. 1;H318 Acute Tox. 3;H331 STOT RE 1;H372 (Larynx.) Aquatic Acute 1;H400 Aquatic Chronic 1;H410 LD50 (Acute toxicity - oral): 1056 mg/kg bw ATE (dust/mist) (Acute toxicity - inhalation): 0.67 mg/l M (acute): 10 M (chronic): 1
Terbutryn	886-50-0 212-950-5	< 0.005 %		Acute Tox. 4;H302 Aquatic Acute 1;H400 Aquatic Chronic 1;H410 LD50 ATE (Acute toxicity - oral): 1000 mg/kg bw M (acute): 100 M (chronic): 100
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 611-341-5 01-2120764691-48	< 0.0015 %		Acute Tox. 3;H301 Acute Tox. 2;H310 Skin Corr. 1B;H314 Skin Sens. 1A;H317 Eye Dam. 1;H318 Acute Tox. 2;H330 Aquatic Acute 1;H400 Aquatic Chronic 1;H410 C ≥ 0.0015%: Skin Sens. 1A;H317 C ≥ 0.6%: Eye Dam. 1;H318 C ≥ 0.6%: Skin Corr. 1C;H314 0.06% ≤ C < 0.6%: Eye Irrit. 2;H319 0.06% ≤ C < 0.6%: Skin Irrit. 2;H315 LD50 (Acute toxicity - dermal): 660 mg/kg bw LD50 (Acute toxicity - oral): 457 mg/kg bw ATE (dust/mist) (Acute toxicity - inhalation): 0.31 mg/l M (acute): 100 M (chronic): 100

Please see section 16 for the full text of H- / EUH-phrases.

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

Ingredient comments: Some products in this product range contain $\geq 1\%$ titanium dioxide (13463-67-7). The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

This product contains micro-encapsulated active substances with controlled release. The ratio between encapsulated and free for each substance are: IPBC 30:1, Terbutryn 56:1. Classification and labeling of this product is based on the free amount of active substance content due to tests made by supplier.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Seek fresh air. Seek medical advice in case of persistent discomfort.

Ingestion: Contact physician if larger quantity has been consumed. Do not induce vomiting.

Skin contact: Wash skin with soap and water.

Eye contact: Flush with water (preferably using eye wash equipment) until irritation subsides. Seek medical advice if symptoms persist.

General: When obtaining medical advice, show the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

The product contains substances that in some cases can cause an allergic reaction on skin contact.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: The product is not directly flammable. Choose extinguishing agents based on the surrounding fire.

Unsuitable extinguishing media: Do not use water stream, as it may spread the fire.

5.2. Special hazards arising from the substance or mixture

The product is not directly flammable. Avoid inhalation of vapour and fumes - seek fresh air.

5.3. Advice for firefighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases - seek fresh air. Avoid unnecessary release to the environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Wear suitable protective clothing. Wear safety goggles if there is a risk of eye splash.

6.2. Environmental precautions

Prevent spillage from entering drains and/or surface water.

6.3. Methods and material for containment and cleaning up

Contain and absorb spill with sand or other absorbent, non-combustible material and transfer to suitable waste containers.

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes. Do not eat, drink or smoke during work.

7.2. Conditions for safe storage, including any incompatibilities

Do not expose to heat (e.g. sunlight). Store frost-free.

7.3. Specific end use(s)

No special uses in addition to identified uses in 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit: Contains no substances subject to reporting requirements.

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

PNEC

Bronopol, cas-no 52-51-7				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
PNEC aqua (freshwater)	0,01 mg/l			
PNEC aqua (marine water)	0,0008 mg/l			
PNEC STP (wastewater-treatment facilities)	0,43 mg/l			
PNEC sediment (freshwater)	0,041 mg/kg			
PNEC sediment (marine water)	0,00328 mg/kg			
PNEC soil	0,5 mg/kg			
1,2-benzisothiazol-3(2H)-one, cas-no 2634-33-5				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
PNEC aqua (freshwater)	4,03 µg/l			
PNEC aqua (intermittent releases (fresh water))	1,1 µg/l			
PNEC aqua (marine water)	403 ng/l			
PNEC aqua (intermittent releases (marine water))	110 ng/l			
PNEC STP (wastewater-treatment facilities)	1,03 mg/l			
PNEC sediment (freshwater)	49,9 µg/kg dw			
PNEC sediment (marine water)	4,99 µg/kg dw			
PNEC soil	3 mg/kg dw			
3-iodo-2-propynyl butylcarbamate, cas-no 55406-53-6				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
PNEC aqua (freshwater)	500 µg/l			
PNEC aqua (marine water)	46 µg/l			
PNEC aqua (intermittent releases)	53 µg/l			
PNEC sediment (freshwater)	0,017 mg/kg dw			
PNEC sediment (marine water)	0,0016 mg/kg dw			
PNEC STP (wastewater-treatment facilities)	440 µg/l			
PNEC soil	5 µg/l			
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), cas-no 55965-84-9				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
PNEC aqua (freshwater)	3,39 µg/l			
PNEC aqua (intermittent releases (fresh water))	3,39 µg/l			
PNEC aqua (marine water)	3,39 µg/l			
PNEC aqua (intermittent releases (marine water))	3,39 µg/l			
PNEC STP (wastewater-treatment facilities)	230 µg/l			
PNEC sediment (marine water)	27 µg/kg dw			

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

PNEC sediment (freshwater)	27 µg/kg dw			
PNEC soil	10 µg/kg dw			

DNEL - workers

Bronopol, cas-no 52-51-7					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal DNEL (long-term exposure - local effects)	0.013 mg/kg bw/day				
Inhalation DNEL (long-term exposure - local effects)	4,2 mg/m³				
Inhalation DNEL (long-term exposure - systemic effects)	4,1 mg/m³				
Dermal DNEL (long-term exposure - systemic effects)	2,3 mg/kg bw/day				
1,2-benzisothiazol-3(2H)-one, cas-no 2634-33-5					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Inhalation DNEL (long-term exposure - systemic effects)	6,81 mg/m³				
Dermal DNEL (long-term exposure - systemic effects)	966 µg/kg bw/day				
3-iodo-2-propynyl butylcarbamate, cas-no 55406-53-6					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Inhalation DNEL (acute/short-term exposure - local effects)	1,16 mg/m³				
Dermal DNEL (long-term exposure - systemic effects)	2 mg/kg bw				
Inhalation DNEL (acute/short-term exposure - systemic effects)	70 mg/m³				
Inhalation DMEL (long-term exposure - local effects)	1,16 mg/m³				
Inhalation DNEL (long-term exposure - systemic effects)	23 mg/m³				
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), cas-no 55965-84-9					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Inhalation DNEL (long-term exposure - local effects)	20 µg/m³				
Inhalation DNEL (acute/short-term exposure - local effects)	40 µg/m³				

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

DNEL - general population

Bronopol, cas-no 52-51-7					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal DNEL (acute/short-term exposure - systemic effects)	4,2 ng/kg bw/day				
Dermal DNEL (acute/short-term exposure - local effects)	0,008 mg/kg bw/day				
Inhalation DNEL (acute/short-term exposure - systemic effects)	3,7 mg/m ³				
Inhalation DNEL (acute/short-term exposure - local effects)	1,3 mg/m ³				
1,2-benzisothiazol-3(2H)-one, cas-no 2634-33-5					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Inhalation DNEL (long-term exposure - systemic effects)	1,2 mg/m ³				
Dermal DNEL (long-term exposure - systemic effects)	345 µg/kg bw/day				
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), cas-no 55965-84-9					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Inhalation DNEL (long-term exposure - local effects)	20 µg/m ³				
Inhalation DNEL (acute/short-term exposure - local effects)	40 µg/m ³				
Oral DNEL (long-term exposure - systemic effects)	90 µg/kg bw/day				
Oral DNEL (acute/short-term exposure - systemic effects)	110 µg/kg bw/day				

8.2. Exposure controls

Appropriate engineering controls: Do not eat, drink or smoke when using this product.

Personal protective equipment, eye/face protection: Wear safety goggles if there is a risk of eye splash.

Personal protective equipment, hand protection: In the event of direct skin contact, wear protective gloves: Change gloves immediately if contaminated, and wash hands with soap and water.
Gloves must conform to EN 374. Type of material and thickness: Nitrile rubber. >0,4 mm.
Penetration time: > 480 min.

Environmental exposure controls: Ensure compliance with local regulations for emissions.

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Parameter	Value/unit
State	Viscous liquid.
Colour	According to product specification
Odour	Weak
Solubility	Soluble in water.

Parameter	Value/unit	Remarks
Odour threshold	No data	
Melting point	~ 0 °C	Water
Freezing point	~ 0 °C	Water
Initial boiling point and boiling range	~ 100 °C	Water
Flammability (solid, gas)		Non-flammable
Flammability limits		Not relevant
Explosion limits		Not relevant
Flash Point		Not applicable.
Auto-ignition temperature		Not relevant
Decomposition temperature:	No data	
pH (solution for use)	8 - 9	
pH (concentrate)		Not relevant
Kinematic viscosity	No data	
Viscosity	No data	
Partition coefficient n-octanol/water	No data	
Vapour pressure	No data	
Density	1000 - 1300 kg/m ³	
Relative density	No data	
Relative vapour density	No data	
Relative density (sat. air)	No data	
Particle characteristics	No data	

9.2. Other information

Parameter	Value/unit	Remarks
Explosive properties		Non-explosive
Oxidising properties		Non-oxidising.

SECTION 10: Stability and reactivity

10.1. Reactivity

Not reactive.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Store frost-free.

10.5. Incompatible materials

Strong oxidisers. Strong alkalis/ Strong acids.

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - oral

1,2-benzisothiazol-3(2H)-one, cas-no 2634-33-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	ATE		450 mg/kg bw			

3-iodo-2-propynyl butylcarbamate, cas-no 55406-53-6

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	LD50		1056 mg/kg bw			

Terbutryn, cas-no 886-50-0

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	LD50 ATE		1000 mg/kg bw			

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), cas-no 55965-84-9

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	LD50		457 mg/kg bw			ECHA

Based on existing data, the classification criteria are deemed not to have been met.
Ingestion of large quantities may cause discomfort.

Acute toxicity - dermal

1,2-benzisothiazol-3(2H)-one, cas-no 2634-33-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	LD50		2000 mg/kg bw			

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), cas-no 55965-84-9

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	LD50		660 mg/kg bw			ECHA

Based on existing data, the classification criteria are deemed not to have been met.

Acute toxicity - inhalation

1,2-benzisothiazol-3(2H)-one, cas-no 2634-33-5

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	ATE (dust/mist)		0.21 mg/l			

3-iodo-2-propynyl butylcarbamate, cas-no 55406-53-6

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	ATE (dust/mist)		0.67 mg/l			

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), cas-no 55965-84-9

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	LC50		1.23 mg/m ³			ECHA
	ATE (dust/mist)		0.31 mg/l			Supplier's Safety Data Sheet

Based on existing data, the classification criteria are deemed not to have been met.

Skin corrosion/irritation: Based on existing data, the classification criteria are deemed not to have been met.

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

Serious eye damage/eye irritation:	Based on existing data, the classification criteria are deemed not to have been met. May cause eye irritation.
Respiratory sensitisation or skin sensitisation:	The product contains small amounts of 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). Persons with a known allergy may exhibit an allergic response to the product.
Germ cell mutagenicity:	Based on existing data, the classification criteria are deemed not to have been met.
Carcinogenic properties:	Based on existing data, the classification criteria are deemed not to have been met.
Reproductive toxicity:	Based on existing data, the classification criteria are deemed not to have been met.
Single STOT exposure:	Based on existing data, the classification criteria are deemed not to have been met.
Repeated STOT exposure:	Based on existing data, the classification criteria are deemed not to have been met.
Aspiration hazard:	Based on existing data, the classification criteria are deemed not to have been met.

11.2. Information on other hazards

Endocrine disrupting properties:	Constituents have no endocrine-disrupting properties with respect to non-target organisms as they do not meet the criteria in Section B of Regulation (EU) 2017/2100.
---	---

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

SECTION 12: Ecological information

12.1. Toxicity

1,2-benzisothiazol-3(2H)-one, cas-no 2634-33-5

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Crustacea	Daphnia magna	21d	21dNOEC	1.2 mg/l		OECD 211	Supplier's Safety Data Sheet
Fish	Oncorhynchus mykiss	48h	48hEC50	3.27 mg/l		OECD 202	Supplier's Safety Data Sheet
Algae	Selenastrum capricornutum	72h	72hNOEC	0.04		OECD 201	Supplier's Safety Data Sheet
Algae	Selenastrum capricornutum	72h	72hEC50	0.11 mg/l		OECD 201	Supplier's Safety Data Sheet
Fish	Oncorhynchus mykiss	28d	28dNOEC	0.21 mg/l		OECD 215	Supplier's Safety Data Sheet
Crustacea	Daphnia magna	48h	48hEC50	3.27 mg/l		OECD 202	Supplier's Safety Data Sheet

3-iodo-2-propynyl butylcarbamate, cas-no 55406-53-6

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Crustacea	Daphnia magna		48hEC50	0.47		OECD 202	
Algae	Pseudokirchneriella subcapitata		72hEC50	0.049		OECD 201	
Fish	Oncorhynchus mykiss		96hLC50	0.145		OECD 203	
Crustacea	Daphnia magna		21dNOEC	0.010		OECD 211	
Fish	Pimephales promelas		28dNOEC	0.014		OECD 210	

Terbutryn, cas-no 886-50-0

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Crustacea	Daphnia magna	48h	48hEC50	2.66 mg/l			
Fish	Lepomis macrochirus	96h	96hLC50	1.3 mg/l			
Crustacea	Daphnia magna	21d	21dNOEC	1.3 mg/l			
Fish	Oncorhynchus mykiss	21d	21dNOEC	0.01			
Algae	Selenastrum capricornutum	168h	EC50	0.013 mg/l			

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), cas-no 55965-84-9

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Fish	Oncorhynchus mykiss	96h	96hLC50	0.22 mg/l		OECD 203	Supplier's Safety Data Sheet
Algae	Skeletonema costatum	48h	48hEC50	0.0052 mg/l		ISO 10253	Supplier's Safety Data Sheet

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

Algae	Skeletonema costatum	48h	48hNOEC	0.00064 mg/l		ISO 10253	Supplier's Safety Data Sheet
Crustacea	Daphnia magna	21d	21dNOEC	0.004 mg/l		OECD 211	Supplier's Safety Data Sheet
Bacteria	Pseudokirchneriella subcapitata	72h	72hNOEC	0.0012 mg/l		OECD 201	Supplier's Safety Data Sheet
Fish	Oncorhynchus mykiss	28d	28dNOEC	0.098 mg/l		OECD 215	Supplier's Safety Data Sheet

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

3-iodo-2-propynyl butylcarbamate, cas-no 55406-53-6

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
				1 - 1.2 days		OECD 308	Supplier's Safety Data Sheet

Test data are not available.

12.3. Bioaccumulative potential

3-iodo-2-propynyl butylcarbamate, cas-no 55406-53-6

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
			#Not translated#	2.8		OECD 117 (1-octanol/water)	Supplier's Safety Data Sheet

Terbutryn, cas-no 886-50-0

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
			Log Pow	3.66			

Test data are not available.

12.4. Mobility in soil

Test data are not available.

12.5. Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances.

12.6. Endocrine disrupting properties

Constituents have no endocrine-disrupting properties with respect to non-target organisms as they do not meet the criteria in Section B of Regulation (EU) 2017/2100.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

If this product as supplied becomes a waste, it meets the criteria of a hazardous waste (Dir. 2008/98/EU). Collect spills and waste in closed, leak-proof containers for disposal at the local hazardous waste site. Uncleansed packaging is to be disposed of via the local waste-removal scheme. Avoid unnecessary release to the environment.

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

Category of waste: 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances
20 01 27* paint, inks, adhesives and resins containing hazardous substances
15 01 04 metallic packaging
15 01 02 plastic packaging

SECTION 14: Transport information

14.1. UN number or ID number:	Not applicable.	14.4. Packing group:	Not applicable.
14.2. UN proper shipping name:	Not applicable.	14.5. Environmental hazards:	Not applicable.
14.3. Transport hazard class(es):	Not applicable.		

14.6. Special precautions for user

14.7. Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Other Information: Chemical safety assessment has not been performed.

SECTION 16: Other information

Other Information: This safety data sheet has been prepared for and applies to this product only. It is based on our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with 1907/2006/EC (REACH) as subsequently changed.

Vendor notes: Changes have been made in sections: -

Hazard statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure. (Larynx.)
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet

Kraso Kolorex Wood Paint Matt

Revision date: 12/05/2025

Supplemental hazard information

EUH208

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Country:

EU