

Product information | TECHNICAL DATA SHEET

WEPRO Multi-Purpose Paint. Solid colors. The easiest spray paint to use for DIY projects and decoration *
400 ml.

GENERAL DESCRIPTION

High-opacity solvent-based multi-surface paint, with excellent outdoor resistance and up to 5 years of anti-corrosive protection. Designed with cutting-edge technology that makes it easy to use, delivering professional-quality results for everyone.

CHARACTERISTICS

- Easy to apply.
- Good gloss retention.
- Highly resistant to outdoor conditions.
- Fast-drying.
- Excellent coverage.
- UV-resistant. (see chart).
- Excellent flexibility.
- Anti-corrosive protection.
- Good hardening.

INSTRUCTIONS FOR USE

- Shake the aerosol thoroughly before use, for about one minute after hearing the mixing ball.
- Apply to clean and dry surfaces. On rusted metal surfaces, first remove the corrosion using a wire brush. On plastics and polyester, first apply an anchoring coat.
- Apply in thin layers for the best results. Recoat after 15 minutes with the same paint, with a maximum of 30 minutes between coats.
- Do not apply too much at once to prevent sagging.
- Turn the aerosol upside down to purge the valve after use. If the cap gets clogged, replace it with a new one.
- Do not apply to equipment or devices that are connected to an electricity supply, and use in well-ventilated areas.
- Request safety data sheets.

PHYSICAL CHARACTERISTICS

Binder type:	Modified alkyd
Color:	See chart
Shine:	Matte <10, Satin 40 – 60, Gloss >70
Touch-dry (ASTM D-1640 ISO 1517):	15' - 30'' ¹
Fully dry (ASTM D-1640 ISO 1517):	24 – 48 h ¹
Coat thickness when dry (ASTM D-823 ISO 2808):	15 µm/layer
Recoat time:	Less than 1 hour between coats.
Salt spray and humidity (ISO 12944-6):	Equivalent to C3 low; ²
Theoretical coverage (continuous painting):	Up to 4.25 m ² (depending on the color)
Product shelf life:	(with proper storage) 6 years
Application conditions:	Minimum ambient temperature: 8°C Surface temperature: 5°C – 35°C Max. humidity 85% R.H.P
Paint heat resistance:	85°C

* Out of all MTN spray paints
¹ This will vary depending on the thickness of the coat applied.
² Internal testing.

APPLICATIONS

Ideal for DIY and professional projects on a variety of surfaces: wood, metal, stainless steel, glass, timber, plaster, ceramic, stone, fabric, paper, papier-mâché, and hard plastic. It can be applied directly without the need for a primer. On difficult surfaces, carry out a test application and/or apply a primer.

Specially designed for both home improvement and professional use: indoor and outdoor furniture, flowerpots, gates, fences, garage doors, bikes, metallic structures, aluminum profiles, industrial and agricultural machinery, urban furniture, etc.

APPEARANCE



CAP

