

Hagmans - Snickerifärg 15

Product Description

Hagmans Carpentry Paint 15 is a water-based paint, based on Hagmans' unique PAA technology. The paint provides a hard yet flexible surface. It has high covering power and is suitable for new or repainting of all types of wooden surfaces or rust-protected metal indoors. For example, doors, kitchen doors, moldings, furniture and most substrates made of primed wood, chipboard, etc. The paint has very good flow, and it remains "open" for a relatively long time to enable subsequent smoothing.

Areas of use

Can be painted on doors, kitchen cabinets, moldings, furniture and most primed wood surfaces.

Technical data:

Parameter	Value	Unit	Method
Area of application	Indoor/Outdoor		
Binder	PU alkyd/acrylate		
Colour	White + Bases		
Completely dry	24 hours		
Density	1,3		
Dust dry	2 hours		
Flammability	Not flammable		
Gloss	15, 40	60°	
Hinding Power	Class 1		
Material consumption	8-10 m²/l		
Re-paintable	8 hours		
Hinding Power	9,4 - EN 13300		
Temperature at painting	Min. +5°C		
Thinner/Cleaning	Water		
Tools for painting	Brush, Roller, Sprayer		
VOC category	(Cat A/d): 130 g/l		
Volume Solids	37%		
Washability	Class 1, EN 13300		
Weight Solids	52%		

Application Instructions

Before Painting

Always start by reading the instructions on the can and remember to be careful from the beginning. Good tools and careful preliminary work are the prerequisites for a successful painting result. Stir the paint well from the bottom before you start painting. Room and surface temperature are also important for the final result. Do not paint if it is colder than +5°C. Wooden surfaces: The surface must be clean, dry and firm. Scrape off old, loose paint. Sand and wash previously painted surfaces with painter's wash and rinse with water and let dry well. Untreated wood indoors should be primed with Snickerigrund. Let dry well before lightly sanding with sandpaper to remove raised fibers. Fill in any unevenness. Sand smooth. Prime with undiluted Snickerigrund, sand with fine sandpaper and wipe clean of dust before finishing painting. Remember to protect floors and furniture properly before you start painting.

Painting

The paint is applied with a suitable high-quality paint brush, paint roller or, after thinning with 10–20% water, with a sprayer. On larger surfaces, the paint can be rolled with a short-haired roller before smoothing with a paint brush. Please test first for best results. Finish with at least 2 coats with time for drying in between.

After Painting

Dry the tools thoroughly before cleaning in water. Close the can tightly after use and store out of reach of children. Liquid paint residues should not be poured down the drain but left at the local environmental station. Paint residues must not be poured down the drain. Metal handles should be separated from the plastic can when recycling the can.

Maintenance

Use a cloth dampened with water and mild detergent to clean the surface. Never use alcohol to clean paint or varnish.