

Product information TECHNICAL DATA SHEET

ANTI-SLIP LACQUER

400 ml, 10.72 Oz, 304 g.

GENERAL DESCRIPTION

Transparent paint formulated with high quality, acrylic resins with non-slip textured finish. All-purpose use for any type of surface.

FEATURES

- Fast drying.
- Excellent elasticity.
- Easy to apply and repaint.
- Good adhesion to multiple surfaces.
- Does not contain lead.
- Strong resistance to wear.
- Class A3 in accordance to UNE-ENV 12633: 2003, Annex A.

APPLICATIONS

Recommended for use on any metal, wood, or concrete surface where an anti-slip finish is required:

- Floors - Stairs - Ramps and entrances - Security

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire brush.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within ten minutes with the same paint.
- During application it is recommended to shake the spray can periodically.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Turn the aerosol upside down to clean out the valve after use. If the nozzle becomes blocked replace it with a new one.
- Request safety datasheets.

PHYSICAL PROPERTIES

Type of liant:	Acrylic
Color:	Transparent
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Totally dry (ASTM D-1640 ISO 1517):	2 h
Dry Coat Thickness (ASTM D-823 ISO 2808):	15 µ/layer
Adherence (ASTM D-3359 ISO 2409):	4 B
Theoretical performance (continuous painting):	2 m² fot 400 ml
Thinner:	Butyl acetate
Product life:	(Stocké correctement) 5 ans
Recoatable:	10'
Condition for application:	Ambient temperature 8°C
	Surface temperature 5°C a 50°C
	Humidity Max. 85 % R.H.P

260126



IMAGE



LABEL



Antideslizante / Anti-Slip Paint
EX014PR1070

CAP SYSTEM



PACKAGING

Capacity 400 ml.
Packaging heat resistance: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

