

Product information | TECHNICAL DATA SHEET

**SEAL-COATING.**

400 ml, 10.68 Oz, 303 g.

**GENERAL DESCRIPTION**

Paint with an elastic base ideal for sealing or repairing waterproof interior or exterior surfaces such as roofs, coverings, plastic metal pipes and any other type of PVC pipe. Create a waterproof and flexible layer that protects and waterproofs all types of surfaces.

**CHARACTERISTICS**

- Fast-drying.
- Excellent flexibility.
- Easy to apply and repaint.
- Excellent adhesion on porous surfaces.
- Excellent weather resistance.
- High sealing and waterproofing potential.
- High opacity.

**APPLICATION**

Due to the characteristics of the product, we recommend its use for the sealing, protection and waterproofing of horizontal and vertical surfaces both indoors and outdoors.

- Terraces, balconies, roofs.
- Metal or plastic pipes (drains, PVC pipes).
- Waterproofing of wet areas. (ponds, aquariums)
- Inside stone, ceramic or wooden plant pots, etc.

**INSTRUCTIONS FOR USE**

- Prepare and properly clean the area to be sealed before applying the product, to ensure effective adhesion.
- Shake the spray can well before use for about one minute after hearing the sound of the mixer ball.
- Apply the product on the area you wish to repair and around it at a distance of 20-30 cm. Apply two or three coats for best results. Depending on the size of the crack, more coats may be necessary.
- Repaint after 20-30' minutes with the same paint.
- Invert the spray can to purge the valve after use. If the cap becomes clogged replace it with a new one.
- Do not apply to plugged-in electronic equipment and use in well-ventilated areas.
- Request safety data sheets.

**GENERAL DESCRIPTION**

Binder type:	Special resin
Color:	Black, teak red y white
Dry to the touch (ASTM D-1640 ISO 1517):	30-45'
Total dry time (ASTM D-1640 ISO 1517):	24 h (2 coats)
Thickness of dry coat (ASTM D-823 ISO 2808):	30 µ/coat
Adherence (ASTM D-3359 ISO 2409):	No aplica
Repainted*:	30'
Repainted with other paints*:	24h
Theoretical performance (continuous painting):	1-1,25 m <sup>2</sup> ; 2 coats (60 µ) 0,6-0,75 m <sup>2</sup>
Shelf life:	5 años (Correctly stored)
Condiciones de aplicacion:	Atmospheric temp. 10-35°C
	Surface temp. 5°-50 C
	Max. Humidity. 85% R.H.P

\* Times may vary depending on thickness of coat.

260126

**IMAGE**



**LABEL**



**CAP SYSTEM**



Negro / Black EX014PIM002	Blanco / White EX014PIM001	Rojo / Red EX014PIM003
------------------------------	-------------------------------	---------------------------

**PACKAGING**

Capacity 400 ml.  
Packaging heat resistance: <50°C  
Propellant: DME

Box (6 units)  
205 X 140 X 200 mm

