

Pigmenterade Tjätroljor

This document applies to: Svart, Lava, Skogsgrå, Tjätbrun, Skogsbrun, Drivved

General

Auson Pigmented Pine tar Oil is a low-viscosity product based on pine tar.

Auson Pigmenterad Tjätrolja penetrates deeply into the wood, prevents drying, and reduces the risk of cracking. Our Pine Tar Products provide effective protection against water penetration and extend the lifespan of the wood. The strong tar scent fades after a few days and is barely noticeable after about a month. The surface can be walked on once all Tjätrolja has been absorbed into the wood.

Auson Pigmenterad Tjätrolja contains various resins and terpenes. Resins are the tree's natural defense against microorganisms and help to heal damage. Our pine tar is produced by heating resin-rich pine wood in a kiln. What makes our Pine Tar Products unique is their high tar content—read more in our brochure at www.Tjätfarg.se.

Areas of Use

Auson Pigmenterad Tjätrolja can be used on untreated wood outdoors such as facades, wooden decks, garden furniture, and other outdoor wooden structures.

Instructions for Use

Read the safety data sheet and the complete painting instructions at: www.Tjätfarg.se

Packaging

0,1 liter can
1 liter can
3 liter can

Technical Data

Density:	1,18 ± 0,03 kg/liter
Solids content (by weight):	60 %
Coverage:	6-10 m ² /liter depending on the substrate
Drying time:	From 24 hours and longer depending on weather conditions, wood type, coating thickness, and how well the tar has been absorbed into the surface
Thinner:	Gum turpentine or denatured alcohol (T-röd)
Cleaning:	Gum turpentine or denatured alcohol (T-röd)

For further information, see the safety data sheet or the instructions on the packaging.

Edition: 2026-04/27 / HA